

TP-LINK 16-Port Gigabit Rackmount Network Switch



Model: TL-SG1016

Manufacturer: TP-LINK

EAN: 6935364020095

Product Code: 200964

R1,447

Static port security: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | MAC address table: 8000 entries | Auto-negotiation: Yes | Cloud-managed: Yes | Port mirroring: Yes | Flow control support: Yes | User operation log: Yes | Copper ethernet cabling technology: 10BASE-T | Cable types supported: Cat3 | Password protection: Yes | Copper ethernet cabling technology: 100BASE-TX | Rack mounting: Yes | VLAN support: Yes | Policy-based routing: Yes | Width: 440 mm | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Configuring Location Settings (CLI): Yes | Traffic shaping: Yes | DHCP features: DHCP snooping | Switch layer: L2 | DHCP features: DHCP client | DHCP features: DHCP server | Switch type: Unmanaged | Access Control List (ACL): Yes | IP routing: Yes | System event log: Yes | Depth: 180 mm | Switching capacity: 32 Gbit/s | Full duplex: Yes | Forwarding rate: 23.8 Mpps | Copper ethernet cabling technology: 1000BASE-T | Head-of-line (HOL) blocking: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Traffic classification: Yes | Height: 44 mm | Heat dissipation: 31.6 BTU/h | IGMP snooping: Yes | Cable types supported: Cat4 | Auto MDI/MDI-X: Yes | Jumbo frames support: Yes | Store-and-forward: Yes | Jumbo frames: 10000 |

Operating temperature (T-T): 0 - 40 °C | Ethernet LAN data rates: 100 | Web-based management:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3i | Ethernet LAN data rates: 800 | Ethernet LAN data rates: 1000 Mbit/s | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 10 | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 480 | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 90% | LED indicators: Yes | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC input voltage: 100 - 240 V | Power consumption (typical): 9.26 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950