

## NETGEAR 28PT GE POE+ Smart Switch



Model: GS728TP-300EUS

Manufacturer: NETGEAR

EAN: 606449162257

Product Code: 203256

## R8,193

GS728TP is Gigabit PoE/ PoE+ Smart Switches that comes with PoE capabilities on all ports and supports PoE+ with up to 30W of power budget on the first 8 ports, providing hardware investment protections so that the switch can support many more PoE powered devices and higher-powered devices down the road. There has also been an addition of high-powered PoE+ Smart Switch into the portfolio. It also comes with 4 dedicated Gigabit SFP ports for fiber connectivity.

Product Description: NETGEAR Smart GS728TP - switch - 24 ports - smart - rack-mountable | Device Type: Switch - 24 ports - L3 Lite - smart | Enclosure Type: Rack-mountable | Subtype: Gigabit Ethernet | Ports: 16 x 10/100/1000 (PoE) + 8 x 10/100/1000 (PoE+) + 4 x SFP | Power Over Ethernet (PoE): PoE+ | PoE Budget: 192 W | Performance: Bandwidth: 56 Gbps | Capacity: Virtual interfaces (VLANs): 256 ACL entries: 480 Multicast groups: 1024 IPv4 routes (static): 32 Packet buffer size: 8 MB | MAC Address Table Size: 8K entries | Jumbo Frame Support: 9KB | Routing Protocol: IGMP, IGMPv2, IGMPv3, MLD, MLDv2 | Remote Management Protocol: RMON 1, RMON 2, RMON 3, RMON 9, SNMP 1, SNMP 2, SNMP 3, HTTPS, TFTP, HTTP | Features: DHCP support, IGMP snooping, DHCP snooping, ACL support, DHCP client, Guest VLAN, broadcast storm protection, Multicast Storm Protection, auto video VLAN, Voice VLAN, Broadcast Storm Control, MLD snooping, block unknown

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

multicast, TCP/UDP proxy, MAC lockdown, Port Security, PoE timer, ingress rate limiting, egress rate limiting, DiffServ support, WRR, SPQ, port mirroring | Compliant Standards: IEEE 802.1x, IEEE 802.1Q, IEEE 802.3ad (LACP), IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1ab (LLDP) | Dimensions (WxDxH): 44 cm x 25.7 cm x 4.4 cm | Weight: 3.73 kg | Localisation: Europe | Manufacturer Warranty: ProSAFE lifetime warranty

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950