

## D-Link DGS-1210-10, Switch



Model: DGS-1210-10/E

Manufacturer: D-LINK

EAN: 790069467707

Product Code: 207745

## R3,084

Produktbeschreibung Der Web Smart Managed Gigabit Switch DGS-1210-10/E unterstützt zahlreiche Features die normalerweise nur in High-End-Switches zu finden sind. Durch den sehr geringen Administrationsaufwand ist er ideal für den Einsatz in kleinen und mittleren Unternehmen geeignet. Der DGS-1210-10 ist mit der D-Link Green Technologie ausgestattet, die den Stromverbrauch und somit die Betriebskosten ohne Leistungseinbußen maßgeblich senkt. Art.-Nr.: 1875564 Typ: Switch | EAN: 0790069467707 | Hersteller-Nr.: DGS-1210-10/E | Bauform: Desktop | Einsatzbereich: Heimnetzwerke, Business | Anschlüsse: 8x (davon: 8x 10/100/1000) | Routing & Switching: Smart Managed, Layer 2 Switching | LEDs: Activity, Power, LAN-Link LEDs: 10x | Stromversorgung: Stromverbrauch Betrieb: 9.4 W | Feature: IGMP v1/v2 Snooping; IGMP per VLAN; Loopback Detection; 802.3ad Link Aggregation; Jumbo Frame: 9K; LLDP; LLDP-MED; STP; RSTP; Flow Control; HOL Blocking Vermeidung; Port Mirroring; Multicast Filtering; 802.1Q; VLAN Gruppierung; Maximal 256 static VLANs Gruppen; Asymmetrisches VLAN; Auto Voice VLAN; QoS, Queue Handling; Bandbreiten Kontrolle; 802.1p Priority Queues; DSCP; ToS; IPv6 Traffic Class; TCP/UDP port; IP Interface; IPv6 Neighbor Discovery (ND); ACL: Priorität / VLAN / MAC / Erther Typ / IP Adresse / DSCP / Protokolltyp; TCP/UDP Port Nummer; IPv6 Traffic Class; Broadcast/Multicast/Unicast Storm Control; D-Link Safeguard Engine; DHCP Server Screening; IP-MAC-Port Binding (Smart Binding); Supports 512

address binding entries; ARP Inspection; ARP + IP Inspection; Supports DHCP Snooping; 802.1X Port-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

based Access Control; ARP Spoofing Prevention: Max. 64 entries; Traffic Segmentation; SSH v2; SSL: Supports v1/v2/v3; Port Security; Supports up to 64 MAC addresses per port; Duplicate address detection; | Weitere Informationen: Web-basiertes UI; TFTP Client; Power Saving nach: Link Status; | Abmessungen: Breite: 280 mm x Höhe: 44 mm x Tiefe/Länge: 126 mm | Gewicht: 1,5 kg

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950