

D-Link DGS- 1100-24V2/E, Switch - black/gray



Model: DGS-1100-24V2/E

Manufacturer: D-LINK

EAN: 790069467844

Product Code: 207746

R3,148

Produktbeschreibung Das DGS-1100-24V2 ist ein leistungsstarker Smart Managed Switch der viel für sein Geld bietet. Er eignet sich hervorragend für KMUs die viel von ihrem Netzwerk fordern wie z.B. die Unterstützung für Überwachung und VoIP. Der DGS-1100-24V2 ist vollgepackt mit Funktionen zum Traffic Management und -optimierung, Management-Tools und Quality of Service. Features wie IGMP-Snooping senden Multicast-Traffic nur dort hin, wo er benötigt wird, wodurch der Netzwerktraffic erheblich reduziert wird Art.-Nr.: 1875563 Typ: Switch | Farbe: schwarz/grau | EAN: 0790069467844 | Hersteller-Nr.: DGS-1100-24V2/E | Bauform: Desktop | Anschlüsse: 24x (davon: 24x 10/100/1000) | Routing & Switching: Smart Managed, Layer 2 Switching | LEDs: Activity, Power, LAN-Link LEDs: 24x | Bedientasten: Reset | Stromversorgung: Netzteilanschluss, Stromverbrauch Betrieb: 14.83 W | Feature: Energy Efficiency Ethernet (EEE), Power Saving By Link Status, Power Saving By LED Shut-Off, Power Saving By Port Shut-Off, Power Saving By System Hibernation, 802.3x Flow Control, Head-of-line (HOL) Blocking Prevention, 802.1D Spanning Tree (STP), 802.1w Rapid Spanning Tree (RSTP), 802.1AX Link Aggregation, 802.3ad Link Aggregation, Loopback Detection

(LBD), Port Mirroring, IGMP Snooping, Max IGMP Snooping Groups 64; 802.1Q VLAN, Port-based

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

VLAN, Voice VLAN, Auto Surveillance VLAN, Asymmetric VLAN, Class of Service (CoS), Two Rate Three Color Marker (trTCM), Rate Limiting, Queue Handling, Strict Priority Queue (SPQ), Weighted Round Robin (WRR), Port-based Bandwidth Control, SSL, Broadcast / Multicast/Unicast Storm Control, Traffic Segmentation, D-Link Safeguard Engine, DoS Attack Prevention, Cable Diagnostics, Simple Network Time Protocol (SNTP), Web-based GUI, SNMP, SNMP Trap, TFTP Client, System Log, LLDP, D-Link Discover Protocol (DDP), DHCP/BootP Client, Dual Images, Ping, D-Link Network Assistant |
Abmessungen: Breite: 280 mm x Höhe: 44 mm x Tiefe/Länge: 180 mm | Gewicht: 1,6 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950