

## ZYXEL GS2220-10HP,EU REGION,8-PORT GBE L2 POE SWITCH WITH GBE UPLINK (1 YEAR NCC PRO PACK LICENSE BUNDLED) (5Y WARRANTY)



Model: GS2220-10HP-EU0101F

Manufacturer: ZYXEL

EAN: 4718937607402

Product Code: 287277

## R7,863

Switch type: Ethernet | Quality of Service (QoS) support: Yes | IGMP snooping: Yes | Broadcast storm control: Yes | SSH/SSL support: Yes | Web-based management: Yes | Networking standards: IEEE

802.3u 100BASE-TX Ethernet

IEEE 802.3ab 1000BASE-T Ethernet

IEEE 802.3z 1000BASE-X

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

IEEE 802.3af PoE

IEEE 802.3at PoE plus

IEEE 802.3az EEE

IEEE 802.3x flow control

IEEE 802.1AB LLDP/LLDP-MED

IEEE 802.3ad LACP aggregation

IEEE 802.1D Spanning Tree Protocol (STP)

IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

IEEE 802.1Q VLAN tagging

IEEE 802.1p Class of Service (CoS) prioritization

IEEE 802.1X port authentication

| MIB support: Zyxel new private MIB

RFC 1066 TCP/IP-based MIB

RFC 1213, 1157 SNMPv2c/v3 MIB

RFC 1493 bridge MIB

RFC 1643 Ethernet MIB

RFC 1757 RMON group 1, 2, 3, 9

RFC 2011, 2012, 2013 SNMPv2 MIB

RFC 2233 SMIPv2 MIB

RFC 2358 Ethernet-like MIB

RFC 2674 bridge MIB extension

RFC 2819, 2925 remote management MIB

RFC 3621 power Ethernet MIB

RFC 4022 management information base for transmission control protocol

RFC 4113 management information base for user datagram protocol

RFC 4292 IP forwarding table MIB

RFC 4293 Management Information Base (MIB) for IP

Cable diagnostic MIB

| Spanning tree protocol: Yes | MAC address filtering: Yes | Security algorithms supported: RADIUS,

TACACS+ | Ethernet LAN (RJ-45) PoE ports quantity: 8 | Power over Ethernet (PoE), W: 180 | Power

consumption, W: 210.8 | Power over Ethernet (PoE) Support: Yes | Ports quantity: 10 | Dimensions W

x D x H, mm: 267 x 162 x 44 | MAC address table, entries: 16000 | Switching capacity, Gbit/s: 20 |

Weight, g: 1300 | Packet transfer speed: 15 Mpps | Certification: LVD, BSMI, FCC Part 15 (Class A), CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(Class A), BSMI ENC, RoHS Level A | Switch layer: L2 | RAM memory: 256 | Flash memory, MB: 32 | SFP/RJ-45 combo ports quantity: 2

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950