

## TP-Link Omada 28-Port Gigabit Smart Switch with 16-Port PoE+



Model: SG2428LP

Manufacturer: TP-LINK

EAN: 8885020620832

Product Code: 298674

## R6,010

Product colour: Grey | Web-based management: Yes | MAC address filtering: Yes | SFP module slots quantity: 4 | Jumbo frames support: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Width: 440 mm | Flow control support: Yes | Power consumption (max): 184.7 W | VLAN support: Yes | Password protection: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Switching capacity: 56 Gbit/s | Spanning tree protocol: Yes | Rack mounting: Yes | Access Control List (ACL): Yes | Networking standards: IEEE 802.3af | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3at | Heat dissipation: 628 BTU/h | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Storage relative humidity (H-H): 5 - 90% | Switch type: Managed | Power over Ethernet plus (PoE+) ports quantity: 16 | Forwarding rate: 41.66 Mpps | Link aggregation: Yes | 10G support: No | DHCP features: DHCP relay | Switch layer: L2/L2+ | Number of VLANs: 4000 | AC input voltage: 100 - 240 V | IGMP snooping: Yes | LED indicators: Yes | DHCP features: DHCP server | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

budget: 150 W | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 4.1 MB | Height: 44 mm | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: Tagged VLAN | Virtual LAN features: Voice VLAN | Multicast support: Yes | Depth: 220 mm | Power source: AC/PoE | Virtual LAN features: MAC address-based VLAN | Jumbo frames: 9000 | Fanless: Yes | Cloud-managed: Yes | ARP inspection: Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950