

**DELL Pro Plus  
P3225DE  
computer  
monitor 80 cm  
(31.5) 2560 x  
1440 pixels  
Wide Quad HD  
LCD Black, Grey**



Model: 210-BRDP

Manufacturer: DELL

EAN: 5397184962503

Product Code: 298941

**R8,492**

Certification: TÜV Rheinland Eye Comfort 3.0 | Adjustable height (max): 15 cm | European Product Registry for Energy Labelling (EPREL) code: 2156641 | Total carbon emissions, w/o use phase (kg of CO2e): 183.843 | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | PAIA version: GaBi version 1, 2024 | Response time measurement type: GTG (Gray to Gray) | Compliance certificates: RoHS | Depth (with stand): 215 mm | Product colour: Black | Display diagonal: 80 cm (31.5") | Width (with stand): 713.4 mm | Cable lock slot: Yes | Power consumption (off): 0.3 W | Display resolution: 2560 x

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

1440 pixels | AC input frequency: 50/60 Hz | HDCP: Yes | Display brightness (typical): 350 cd/m<sup>2</sup> | AC input voltage: 100 - 240 V | Native aspect ratio: 16:9 | LED indicators: Yes | Tilt angle range: -5 - 21° | DisplayPorts quantity: 2 | Ethernet LAN data rates: 1000 Mbit/s | Response time: 8 ms | LED backlight: Yes | Supported graphics resolutions: 1280 x 1024 (SXGA) | Contrast ratio (typical): 1500:1 | Supported graphics resolutions: 1600 x 1200 | Viewing angle, horizontal: 178° | Cable lock slot type: Kensington | Supported graphics resolutions: 720 x 400 | Height adjustment: Yes | HD type: Wide Quad HD | On Screen Display (OSD): Yes | Storage temperature (T-T): -20 - 60 °C | Supported graphics resolutions: 2560 x 1440 | Panel type: IPS | DisplayPort cable length: 1.8 m | Power consumption (typical): 23.1 W | Swivelling: Yes | Low Blue Light technology: Yes | Display technology: LCD | Input current: 2.8 A | HDCP version: 1.4 | Response time (fast): 5 ms | Supported video modes: 720p | USB Type-C downstream ports quantity: 1 | Mac operating systems supported: Yes | Touchscreen: No | sRGB coverage (typical): 99% | Viewing angle, vertical: 178° | Supported video modes: 576p | Viewable size, vertical: 39.3 cm | Operating altitude: 0 - 5000 m | USB Type-C DisplayPort Alternate Mode: Yes | Surface hardness: 3H | Supported video modes: 480p | Supported video modes: 1080p | Pivot: Yes | Viewable size, horizontal: 69.8 cm | Power supply type: Internal | Cable management: Yes | Dell Display Manager (DDM) compatibility: Yes | Supported graphics resolutions: 640 x 480 (VGA) | Dell ComfortView technology: Yes | Vertical scan range: 48 - 100 Hz | Anti-glare screen: Yes | Supported graphics resolutions: 1152 x 864 (XGA+) | Operating temperature (T-T): 0 - 40 °C | Built-in speaker(s): No | Headphone out: No | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | Storage relative humidity (H-H): 5 - 90% | Heat dissipation (typical): 78.8 BTU/h | Supported graphics resolutions: 1024 x 768 (XGA) | Pivot angle: -90 - 90° | Number of USB Type-C upstream ports quantity: 1 | Weight (with stand): 9.14 kg | Power consumption (max): 192 W | HDMI: Yes | Screen shape: Flat | Stand included: Yes | Total carbon footprint (kg of CO<sub>2</sub>e): 297 | Display number of colours: 1.07 billion colours | Energy efficiency scale: A to G | Panel mounting interface: 100 x 100 mm | Built-in USB hub: Yes | Maximum refresh rate: 100 Hz | Operating relative humidity (H-H): 10 - 80% | Wake-on-LAN: Yes | Backlight type: Edge LED | Built-in camera: No | Weight (without stand): 6.63 kg | Pixel pitch: 0.2727 x 0.2727 mm | DisplayPort version: 1.4 | Swivel angle range: -30 - 30° | Height (without stand): 413.1 mm | Horizontal scan range: 30 - 151 kHz | VESA mounting: Yes | Tilt adjustment: Yes | Bezel width (side): 7.64 mm | Width (without stand): 713.4 mm | Height (with stand): 619 mm | Bezel width (bottom): 1.3 cm | Front bezel colour: Black | Plug and Play: Yes | Non-operating altitude: 0 - 12192 m | USB Power Delivery up to: 90 W | USB Type-A downstream ports quantity: 3 | Bezel width (top): 7.45 mm | Power consumption (standby): 0.4 W | Pixel density: 93 ppi | Feet colour: Grey | Viewable size diagonal: 80.1 cm | Flicker-free

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

technology: Yes | Depth (without stand): 50 mm | Package weight: 12.9 kg | Cables included: USB Type-C | Cables included: DisplayPort | Cables included: USB Type-A to USB Type-C | USB Power Delivery (USB PD): Yes | Carbon emissions, logistics (kg of CO2e): 24.354 | NVIDIA G-SYNC: No | AMD FreeSync: No | Windows operating systems supported: Windows 10 | Energy efficiency class (HDR): Not available | Energy consumption (SDR) per 1000 hours: 23 kWh | Doesn't contain: Arsenic | Doesn't contain: PVC/BFR | Doesn't contain: Mercury | Sustainability certificates: EPEAT Climate + | Sustainability certificates: EPEAT Gold | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Energy efficiency class (SDR): E | Carbon emissions, end-of-life (kg of CO2e): 28.512 | Carbon emissions, energy usage (kg of CO2e): 113.157 | Carbon emissions, manufacturing (kg of CO2e): 130.977

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950