

LG 29U511A-B computer monitor 73.7 cm (29) 2560 x 1080 pixels WFHD LCD Black



Model: 29U511A-B

Manufacturer: LG

EAN: 8806096534601

Product Code: 298944

R3,507

Energy consumption (SDR) per 1000 hours: 20 kWh | Energy consumption (HDR) per 1000 hours: 22 kWh | Energy efficiency class (SDR): E | Energy efficiency class (HDR): F | DisplayPort out version: 1.4 | European Product Registry for Energy Labelling (EPREL) code: 2329253 | Display resolution: 2560 x 1080 pixels | Display number of colours: 16.7 million colours | Display brightness (typical): 250 cd/m² | AC input frequency: 50/60 Hz | Product colour: Black | DisplayPorts quantity: 1 | Response time: 5 ms | HD type: WFHD | Depth (with stand): 220 mm | Height (with stand): 408.7 mm | Viewing angle, horizontal: 178° | AC input voltage: 100 - 240 V | Native aspect ratio: 21:9 | Viewing angle, vertical: 178° | Display diagonal: 73.7 cm (29") | Package weight: 6.6 kg | Width (with stand): 688.5 mm | VESA mounting: Yes | Display diagonal (metric): 73 cm | Weight (with stand): 5.1 kg | Panel type: IPS | HDMI: Yes | Height (without stand): 313.4 mm | Width (without stand): 688.5 mm | Package width:

781 mm | Tilt adjustment: Yes | HDMI ports quantity: 1 | Depth (without stand): 76.9 mm | High

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10) | High Dynamic Range (HDR) supported: Yes | Maximum refresh rate: 100 Hz | Panel mounting interface: 100 x 100 mm | Headphone out: Yes | Package height: 391 mm | Contrast ratio (typical): 1000:1 | Package depth: 132 mm | Pixel pitch: 0.26 x 0.26 mm | Weight (without stand): 4 kg | Cables included: HDMI | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Response time measurement type: GTG (Gray to Gray)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950