

TP-Link 28-Port Gigabit Easy Smart Switch with 24-Port PoE+



Model: TL-SG1428PE

Manufacturer: TP-LINK

EAN: 6935364072209

Product Code: 298981

R5,312

Certification: CE, FCC, RoHS | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Web-based management: Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Product colour: Black | Networking standards: IEEE 802.3at | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3u | AC input frequency: 50 - 60 Hz | 10G support: No | Multicast support: Yes | Depth: 220 mm | Store-and-forward: Yes | Jumbo frames support: Yes | Broadcast storm control: Yes | IGMP snooping: Yes | Cable types supported: Cat6 | Cable types supported: Cat3 | Package weight: 3.94 kg | Power source: AC | Cable types supported: Cat4 | Power over Ethernet (PoE): Yes | Rack mounting: Yes | Height: 44 mm | Package depth: 528 mm | Cables included: AC | Virtual LAN features: Tagged VLAN | Number of VLANs: 32 | Width: 440 mm | MAC address table: 8000 entries | Auto-negotiation: Yes | Total Power over Ethernet (PoE) budget: 250 W | Security algorithms: SNMP | Security algorithms: SNMPv2 | Gigabit Ethernet (copper) ports quantity: 26 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Jumbo frames: 10000 | Auto MDI/MDI-X: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Link aggregation: Yes | Number of fans: 2 fan(s) | Harmonized System (HS) code: 85176990 | User guide: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Flow control support: Yes | Operating temperature (T-T): 0 - 50 °C | Rate limiting: Yes | Operating relative humidity (H-H): 10 - 90% | Virtual LAN features: Port-based VLAN | Rack mount kit: Yes | Security algorithms: SNMPv3 | Basic switching RJ-45 Ethernet ports quantity: 26 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package width: 336 mm | Switch layer: L2 | Form factor: 1U | Storage relative humidity (H-H): 5 - 90% | Packet buffer memory: 4.1 MB | Port mirroring: Yes | VLAN support: Yes | Warnings: Do not open the case or try to repair it yourself. | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Number of queues: 4 | Package height: 100 mm | Warnings: Ensure the unit is adequately ventilated during operation. | Switch type: Managed | Copper ethernet cabling technology: 1000BASE-T | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Fiber ethernet cabling technology: 1000BASE-X | Power supply included: Yes | Power consumption (max): 1039.03 W | Forwarding rate: 41.7 Mpps | SFP module slots quantity: 2 | Switching capacity: 56 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 24

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950