

AG Neovo QM-4303 Flat panel monitor Digital Signage 43 500 cd/m 4K Ultra HD Black



Model: QM-4303

Manufacturer: AG NEOVO

EAN: 4710739598605

Product Code: 298990

R12,829

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Energy consumption (SDR) per 1000 hours: 99 kWh | Energy efficiency class (SDR): G | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: WEEE | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: REACH | Hazard pictogram(s): GHS09: Environmental hazard | Warnings: Do not open the appliance housing, risk of electric shock. | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Hazard pictogram(s): GHS07: Harmful | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Haze rate: 25% | Display brightness: 500 cd/m² | VGA (D-Sub) input ports: 1 | Surface hardness: 3H | USB port: Yes | Panel type: VA | Display depth: 70 mm | Number of built-in speakers: 2 | Display width: 971 mm | Operating hours (hours/days): 24/7 | Energy efficiency scale: A to G | Anti-glare screen: Yes | Mounting type: Wall | Built-in speaker(s): Yes | Remote control

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

included: Yes | Power consumption (standby): 0.5 W | USB ports quantity: 1 | Orientation: Horizontal/Vertical | Display weight: 8 kg | USB version: 2.0 | Placement supported: Indoor | Display height: 559 mm | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | Remote (IR) output: 1 | USB playback: Yes | Built-in processor: No | Purpose: Universal | PC Audio in: Yes | Computer system: No | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN: Yes | Pixel pitch: 0.245 x 0.245 mm | Storage temperature (T-T): 20 - 80 °C | Viewing angle, horizontal: 178° | Package width: 1075 mm | AC input voltage: 100 - 240 V | Touchscreen: No | Ethernet LAN (RJ-45) ports: 1 | Horizontal scan range: 15 - 135 kHz | DVI port: No | Cable lock slot type: Kensington | Cables included: HDMI | Batteries included: Yes | Package depth: 144 mm | Power consumption (typical): 102 W | Display number of colours: 1,07G | Power consumption (off): 0.3 W | Display diagonal: 109.2 cm (43") | Response time: 5 ms | Package weight: 11.5 kg | HD type: 4K Ultra HD | Product design: Digital signage flat panel | Viewing angle, vertical: 178° | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | Native aspect ratio: 16:9 | Wi-Fi: No | VESA mounting: Yes | Product colour: Black | Panel mounting interface: 300 x 300 mm | Cables included: AC | HDMI version: 2.0 | Package height: 652 mm | RS-232 interface: Yes | HDMI ports quantity: 2 | Operating relative humidity (H-H): -20 - 60% | AC input frequency: 50 - 60 Hz | Display resolution: 3840 x 2160 pixels

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950