

AG Neovo QM-5503 Flat panel monitor Digital Signage 55 500 cd/m 4K Ultra HD Black



Model: QM-5503

Manufacturer: AG NEOVO

EAN: 4710739598612

Product Code: 298991

R15,762

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Energy efficiency class (SDR): G | Energy consumption (SDR) per 1000 hours: 134 kWh | Display brightness: 500 cd/m² | Batteries included: Yes | USB ports quantity: 1 | USB version: 2.0 | Mounting type: Wall | DVI port: No | Anti-glare screen: Yes | Display depth: 70 mm | VGA (D-Sub) input ports: 1 | Built-in speaker(s): Yes | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | Number of built-in speakers: 2 | Operating hours (hours/days): 24/7 | HDMI ports quantity: 2 | Power consumption (standby): 0.5 W | Remote control included: Yes | Remote (IR) output: 1 | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Hazard pictogram(s): GHS07: Harmful | Hazard pictogram(s): GHS09: Environmental hazard | Warnings: Do not open the appliance housing, risk of electric shock. | Display weight: 13 kg | Wi-Fi: No | VESA mounting: Yes | Computer system: No | USB port: Yes | Energy efficiency scale: A to G | Warnings: The product should be disposed of by

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

specialist disposal facilities for electronic equipment. | Built-in processor: No | Purpose: Universal | Haze rate: 25% | Panel type: VA | Display height: 709.2 mm | Ethernet LAN: Yes | HDMI version: 2.0 | Orientation: Horizontal/Vertical | Touchscreen: No | PC Audio in: Yes | Placement supported: Indoor | Compliance certificates: WEEE | Compliance certificates: Low Voltage Directive (LVD) | Display width: 1238.4 mm | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: REACH | RS-232 interface: Yes | Panel mounting interface: 300 x 300 mm | USB playback: Yes | Surface hardness: 3H | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): 0 - 40 °C | Horizontal scan range: 15 - 135 kHz | HD type: 4K Ultra HD | Package depth: 144 mm | Storage temperature (T-T): 20 - 80 °C | Product colour: Black | Viewing angle, vertical: 178° | Power consumption (typical): 102 W | Native aspect ratio: 16:9 | Display resolution: 3840 x 2160 pixels | Package height: 830 mm | Operating relative humidity (H-H): -20 - 60% | Response time: 5 ms | AC input frequency: 50 - 60 Hz | Viewing angle, horizontal: 178° | Power consumption (off): 0.3 W | Cable lock slot type: Kensington | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | Package width: 1390 mm | Package weight: 17.6 kg | AC input voltage: 100 - 240 V | Display diagonal: 139.7 cm (55") | Cables included: AC | Cables included: HDMI | Display number of colours: 1,07G | Pixel pitch: 0.245 x 0.245 mm | Product design: Digital signage flat panel

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950