

TP-Link Omada 16-Port Gigabit Smart Switch with 2 SFP Slots



Model: TL-SG2218

Manufacturer: TP-LINK

EAN: 6935364006419

Product Code: 299250

R2,963

Certification: CE, FCC, RoHS | Cables included: AC | Flow control support: Yes | Product colour: Black | Storage relative humidity (H-H): 5 - 90% | VLAN support: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Rack mounting: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | ARP inspection: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | BPDU filtering/protection: Yes | Operating temperature (T-T): 0 - 40 °C | Power consumption (max): 12.3 W | Height: 44 mm | Depth: 180 mm | Virtual LAN features: Tagged VLAN | Quick start guide: Yes | DHCP features: DHCPv6 snooping | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | Form factor: 1U | Cloud-managed: Yes | Forwarding rate: 26.8 Mpps | Power over Ethernet (PoE): No | Width: 440 mm | Virtual LAN features: Voice VLAN | DHCP features: DHCP server | Management protocols: SNMPv1/v2c/v3, SNTP | MAC address table: 8000 entries | SFP module slots quantity: 2 | Multicast support: Yes | Cables included: LAN (RJ-45) | Web-based management: Yes | Networking standards: IEEE 802.3ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3i | Switch layer: L2/L2+ | System event log: Yes | Networking standards: IEEE 802.3z | Number of VLANs: 4000 | 10G support: No | SSH/SSL support: Yes | Storage

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power source: AC | Power supply included: Yes | Switching capacity: 36 Gbit/s | Operating relative humidity (H-H): 10 - 90% | Rate limiting: Yes | Networking standards: IEEE 802.3u | MIB support: Yes | DHCP features: DHCPv6 client | Virtual LAN features: Private VLAN | Virtual LAN features: Port-based VLAN | AC input voltage: 100 - 240 V | Virtual LAN features: Protocol-based VLAN | Switch type: Managed | Number of IP interfaces: 16 | Access Control List (ACL): Yes | Loop protection: Yes | LED indicators: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Heat dissipation: 41.97 BTU/h | Static route: Yes | AC input frequency: 50/60 Hz | IGMP snooping: Yes | Number of static routes: 32 | Fanless: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Link aggregation: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Jumbo frames support: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Store-and-forward: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950