

Ubiquiti UniFi Express 7 gateway/controller 10, 100, 1000, 2500, 10000 Mbit/s



Model: UX7

Manufacturer: UBIQUITI

EAN: 810010074300

Product Code: 299267

R4,440

WLAN data transfer rates supported: 6.5 | WLAN data transfer rates supported: 2 | WLAN data transfer rates supported: 9 | WLAN data transfer rates supported: 11 | WLAN data transfer rates supported: 6 | Processor frequency: 1500 MHz | WLAN data transfer rates supported: 48 | WLAN data transfer rates supported: 5.5 | Ethernet LAN data rates: 100 | WAN connection: Ethernet (RJ-45) | Networking standards: IEEE 802.1Q | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 10000 Mbit/s | WLAN data transfer rates supported: 36 | WLAN data transfer rates supported: 300 Mbit/s | Ethernet LAN data rates: 2500 Mbit/s | WLAN data transfer rates supported: 1 | Display diagonal: 2.44 cm (0.96") | WLAN data transfer rates supported: 18 | WLAN data transfer rates supported: 12 | WLAN data transfer rates supported: 24 | WLAN data transfer rates supported: 54 | Bluetooth: Yes | Frequency band: 2.4, 5, 6 GHz | Antenna type: Internal

| Reset button: Yes | Product colour: White | Compliance certificates: Federal Communications

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Commission (FCC) | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Electromagnetic (EMP) protection: Yes | Electromagnetic (EMP) protection (contact): 4 kV | Electromagnetic (EMP) protection (air): 8 kV | Processor family: ARM Cortex | Operating relative humidity (H-H): 5 - 95% | Processor model: Cortex-A53 | Number of processors installed: 1 | Display type: LCM | Width: 117 mm | AC adapter included: Yes | Internal memory: 3000 MB | Input voltage: 100 - 240 V | Quality of Service (QoS) support: Yes | Built-in processor: Yes | Weight: 422 g | Power consumption (max): 22 W | LED indicators: Status | Antennas quantity: 4 | Wi-Fi: Yes | Processor manufacturer: ARM | Firewall security: Yes | Input current: 5 A | Wireless connection: Yes | VLAN support: Yes | Antenna gain level (max): 6 dBi | Cables included: Power | Cables included: LAN (RJ-45) | Depth: 117 mm | Multicast support: Yes | Security algorithms: IPSec | Security algorithms: WPA | Operating temperature (T-T): -10 - 40 °C | Security algorithms: PPSK | Data transfer rate: 5.7 Gbit/s | Security algorithms: WPA-PSK | Security algorithms: WPA3 | Security algorithms: WPA2 | Security algorithms: WPA-Enterprise | Ethernet LAN (RJ-45) ports: 2 | Routing protocols: OSPF | Security algorithms: TLS | Height: 42.5 mm | DHCP server: Yes | Security algorithms: 802.1x RADIUS | Load balancing: Yes | Enclosure material: Polycarbonate (PC) | Control display unit: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950