

TP-Link Omada SG5428X network switch Managed L3 Gigabit Ethernet (10/100/1000) Black



Model: SG5428X

Manufacturer: TP-LINK

EAN: 8885020626421

Product Code: 299291

R9,606

AC input voltage: 100 - 240 V | Processor frequency: 1200 MHz | LED indicators: Yes | USB 2.0 ports quantity: 1 | Security algorithms: SNMPv3 | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Networking standards: IEEE 802.3af | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Operating temperature (T-T): -5 - 45 °C | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3bt | Storage relative humidity (H-H): 5 - 90% | Security algorithms: SNMP | Product colour: Black | Quick start guide: Yes | Power consumption (max): 19.6 W | Power over Ethernet (PoE): No | Firmware upgradeable: Yes | Processor manufacturer: ARM | Heat dissipation: 66.87 BTU/h | Forwarding rate: 95.23 Mpps | Switch type:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Managed | Height: 44 mm | Mean time between failures (MTBF): 519.543 h | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | USB Type-C ports quantity: 1 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switching capacity: 128 Gbit/s | Memory type: DRAM | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Jumbo frames: 9000 | Cables included: AC | Surge protection voltage: 6 kV | Built-in processor: Yes | Virtual LAN features: Private VLAN | Bandwidth: 64 Gbit/s | IP-MAC-Port binding: Yes | Telnet: Yes | Packet buffer memory: 12 MB | Console port: RJ-45 | MAC address table: 16000 entries | Virtual LAN features: Voice VLAN | Multicast support: Yes | Virtual LAN features: Protocol-based VLAN | Depth: 180 mm | Virtual LAN features: MAC address-based VLAN | Power source: AC | Jumbo frames support: Yes | Link aggregation: Yes | Store-and-forward: Yes | Surge protection: Yes | Port mirroring: Yes | Stackable: Yes | ARP inspection: Yes | Width: 440 mm | Rack mounting: Yes | IGMP snooping: Yes | Compliance certificates: Federal Communications Commission (FCC) | Password protection: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Flash memory: 512 MB | Basic switching RJ-45 Ethernet ports quantity: 24 | VLAN support: Yes | Internal memory: 2000 MB | DHCP features: DHCP server | DHCP features: DHCP relay | SSH/SSL support: Yes | Switch layer: L3 | Number of VLANs: 4000 | Rack mount kit: Yes | Power supply included: Yes | Static port security: Yes | 10G support: Yes | Management level: 4 | Cloud-managed: Yes | Fanless: Yes | Physical stacking (units): 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950