

## TP-Link 24-Port 10/100Mbps + 2- Port Gigabit Unmanaged PoE+ Switch



Model: TL-SL1226P

Manufacturer: TP-LINK

EAN: 6935364089443

Product Code: 299300

## R3,841

Certification: CE, FCC, RoHS | Traffic classification: Yes | Forwarding rate: 6.54 Mpps | Combo SFP ports quantity: 2 | Power over Ethernet plus (PoE+) ports quantity: 24 | Rack mount kit: Yes | Gigabit Ethernet (copper) ports quantity: 2 | Store-and-forward: Yes | Fast Ethernet (copper) ports quantity: 24 | Auto-negotiation: Yes | Jumbo frames: 10000 | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | MAC address table: 8000 entries | Number of fans: 2 fan(s) | Switch type: Unmanaged | LED indicators: Yes | Auto MDI/MDI-X: Yes | Heat dissipation: 1002.54 BTU/h | Product colour: Grey | Package depth: 528 mm | 10G support: No | Quick start guide: Yes | Storage temperature (T-T): -40 - 70 °C | Switching capacity: 8.8 Gbit/s | Power source: AC | AC input voltage: 100 - 240 V | Power consumption (max): 281 W | Packet buffer memory: 4.1 MB | Operating relative humidity (H-H): 10 - 90% | Copper ethernet cabling technology:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

10BASE-T | Jumbo frames support: Yes | Copper ethernet cabling technology: 100BASE-TX | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Total Power over Ethernet (PoE) budget: 250 W | Form factor: 1U | Networking standards: IEEE 802.3at | Package width: 250 mm | Operating temperature (T-T): 0 - 50 °C | Networking standards: IEEE 802.3af | Package weight: 3.02 kg | Networking standards: IEEE 802.3x | Height: 44 mm | Basic switching RJ-45 Ethernet ports quantity: 26 | Copper ethernet cabling technology: 1000BASE-T | Depth: 180 mm | Package height: 80 mm | Harmonized System (HS) code: 85176990 | Rack mounting: Yes | Storage relative humidity (H-H): 5 - 90% | Power supply included: Yes | Width: 440 mm | Power over Ethernet (PoE): Yes

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950