

iiyama G- MASTER G2741HSU-B1 computer monitor 68.6 cm (27) 1920 x 1080 pixels Full HD Black



Model: G2741HSU-B1

Manufacturer: IIYAMA

EAN: 4948570126330

Product Code: 299390

R2,682

Certification: CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA | Warnings: Do not expose to water or excessive moisture. | Warnings: The monitor contains materials that may be harmful to the environment follow local regulations for the disposal of electronic devices. | Warnings: Avoid direct contact with liquids. | Response time (MPRT): 1 ms | Number of downstream ports: 2 | Tilt angle range: -4 - 22° | Power consumption (typical): 16 W | HD type: Full HD | Storage temperature (T-T): -20 - 60 °C | Contrast ratio (dynamic): 8000000:1 | Package weight: 5.3 kg | RMS rated power: 4 W | Quick start guide: Yes | Built-in USB hub: Yes | NVIDIA G-SYNC type: G-SYNC

Compatible | Cables included: HDMI | Cables included: USB | Display surface: Matt | Cable lock slot

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

type: Kensington | HDMI cable length: 1.5 m | Number of OSD languages: 11 | Display brightness (typical): 350 cd/m² | Number of speakers: 2 | Power supply type: Internal | Built-in speaker(s): Yes | Energy efficiency class (SDR): C | Weight (with stand): 4 kg | Headphone out: Yes | VESA Adaptive Sync support: Yes | Input current: 1.7 A | DisplayPorts quantity: 1 | USB hub version: 2.0 | Operating relative humidity (H-H): 10 - 80% | Viewing angle, horizontal: 178° | AC input voltage: 100 - 240 V | Operating temperature (T-T): 5 - 35 °C | Power consumption (off): 0.3 W | Energy efficiency scale: A to G | Package depth: 688 mm | Width (with stand): 611.5 mm | Contrast ratio (typical): 1500:1 | Native aspect ratio: 16:9 | Energy efficiency class (HDR): Not available | Viewable size, horizontal: 59.8 cm | Cables included: AC | Storage relative humidity (H-H): 10 - 90% | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Low Blue Light technology: Yes | Power consumption (standby): 0.5 W | On Screen Display (OSD) languages: Multi | Flicker-free technology: Yes | Product colour: Black | HDCP: Yes | Screen shape: Flat | Height adjustment: No | Maximum refresh rate: 144 Hz | VESA mounting: Yes | DisplayPort version: 1.2 | Viewable size, vertical: 33.6 cm | Height (with stand): 432 mm | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 163 kHz | Pixel pitch: 0.311 x 0.311 mm | Panel mounting interface: 100 x 100 mm | Package width: 688 mm | Cable lock slot: Yes | Display number of colours: 16.7 million colours | HDMI: Yes | Tilt adjustment: Yes | Package height: 442 mm | Energy consumption (SDR) per 1000 hours: 14 kWh | Power cable length: 1.5 m | AMD FreeSync: Yes | HDMI version: 1.4 | Display diagonal (metric): 68.6 cm | Depth (with stand): 349 mm | Built-in camera: No | Touchscreen: No | Panel type: IPS | Market positioning: Gaming | HDMI ports quantity: 1 | DDC/CI: Yes | NVIDIA G-SYNC: Yes | Display diagonal: 68.6 cm (27") | European Product Registry for Energy Labelling (EPREL) code: 2422731

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950