

**iiyama G-
MASTER
GB2741HSU-B1
computer
monitor 68.6 cm
(27) 1920 x
1080 pixels Full
HD LED Black**



Model: GB2741HSU-B1

Manufacturer: IIYAMA

EAN: 4948570126347

Product Code: 299391

R2,956

Certification: CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA | Adjustable height (max): 15 cm | Number of downstream ports: 2 | Pivot: Yes | Swivelling: Yes | Display technology: LED | NVIDIA G-SYNC type: G-SYNC Compatible | Pivot angle: 0 - 90° | USB hub version: 2.0 | On Screen Display (OSD): Yes | Built-in camera: No | Height adjustment: Yes | Tilt adjustment: Yes | Flicker-free technology: Yes | On Screen Display (OSD) languages: Multi | Built-in speaker(s): Yes | Display diagonal (metric): 68.6 cm | Power consumption (standby): 0.5 W | sRGB coverage (typical): 100% | Viewable size, vertical: 33.6 cm | Number of speakers: 2 | Headphone out: Yes |

Swivel angle range: -45 - 45° | Number of OSD languages: 11 | Warnings: Avoid direct contact with

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

liquids. | Power cable length: 1.5 m | VESA mounting: Yes | Warnings: The monitor contains materials that may be harmful to the environment follow local regulations for the disposal of electronic devices. | Viewable size, horizontal: 59.8 cm | Maximum refresh rate: 144 Hz | Warnings: Do not expose to water or excessive moisture. | HDMI cable length: 1.5 m | Energy efficiency scale: A to G | Response time (MPRT): 1 ms | Panel mounting interface: 100 x 100 mm | Weight (with stand): 5.4 kg | HDMI: Yes | RMS rated power: 4 W | Contrast ratio (typical): 1500:1 | Panel type: IPS | Market positioning: Gaming | Colour gamut standard: sRGB | European Product Registry for Energy Labelling (EPREL) code: 2423143 | Energy efficiency class (SDR): C | Energy efficiency class (HDR): Not available | Energy consumption (SDR) per 1000 hours: 14 kWh | VESA Adaptive Sync support: Yes | AMD FreeSync: Yes | DDC/CI: Yes | Touchscreen: No | Height (without stand): 402 mm | Low Blue Light technology: Yes | Power supply type: Internal | Cable management: Yes | HDCP: Yes | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Tilt angle range: -5 - 23° | HDMI version: 1.4 | Display brightness (typical): 350 cd/m² | Cable lock slot: Yes | Pixel pitch: 0.311 x 0.311 mm | DisplayPorts quantity: 1 | Operating relative humidity (H-H): 10 - 80% | NVIDIA G-SYNC: Yes | Width (with stand): 611.5 mm | Contrast ratio (dynamic): 80000000:1 | Power consumption (typical): 16 W | Quick start guide: Yes | Cable lock slot type: Kensington | HD type: Full HD | Display surface: Matt | Storage relative humidity (H-H): 10 - 90% | Viewing angle, vertical: 178° | Native aspect ratio: 16:9 | Display diagonal: 68.6 cm (27") | Depth (with stand): 390.5 mm | Display number of colours: 16.7 million colours | Input current: 1.5 A | Built-in USB hub: Yes | DisplayPort version: 1.2 | Height (with stand): 552 mm | Horizontal scan range: 30 - 163 kHz | Operating temperature (T-T): 5 - 35 °C | Package height: 442 mm | Product colour: Black | Viewing angle, horizontal: 178° | Package depth: 691 mm | Screen shape: Flat | HDMI ports quantity: 1 | AC input voltage: 100 - 240 V | Power consumption (off): 0.3 W | Storage temperature (T-T): -20 - 60 °C | Cables included: USB | Cables included: AC | Package weight: 6.8 kg | Package width: 691 mm | Cables included: HDMI

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950