

**iiyama G-
MASTER
GB2771QSU-B1
computer
monitor 68.6 cm
(27) 2560 x
1440 pixels
Wide Quad HD
Black**



Model: GB2771QSU-B1

Manufacturer: IIYAMA

EAN: 4948570126514

Product Code: 299405

R4,174

Certification: CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA | Power consumption (off): 0.3 W | Display diagonal: 68.6 cm (27") | Product colour: Black | Display brightness (typical): 350 cd/m² | Tilt angle range: -5 - 23° | Cable lock slot: Yes | Display resolution: 2560 x 1440 pixels | AC input frequency: 50/60 Hz | Width (with stand): 613.5 mm | Native aspect ratio: 16:9 | Warnings: Do not expose to water or excessive moisture. | European Product Registry for Energy Labelling (EPREL) code: 2436003 | Warnings: The monitor contains materials that may be

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

harmful to the environment follow local regulations for the disposal of electronic devices. | Response time (MPRT): 0.5 ms | DisplayPorts quantity: 1 | Built-in speaker(s): Yes | Package width: 690 mm | HDMI: Yes | On Screen Display (OSD) languages: Multi | Low Blue Light technology: Yes | Pivot angle: 0 - 90° | Power supply type: Internal | Cable management: Yes | Headphone out: Yes | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Colour depth: 10 bit | DDC/CI: Yes | HDMI ports quantity: 2 | Package depth: 465 mm | Package height: 140 mm | Market positioning: Gaming | On Screen Display (OSD): Yes | Energy efficiency scale: A to G | VESA Adaptive Sync support: Yes | Height adjustment: Yes | HD type: Wide Quad HD | Maximum refresh rate: 200 Hz | Viewable size, horizontal: 59.7 cm | Panel type: Fast IPS | HDCP: Yes | Energy consumption (HDR) per 1000 hours: 36 kWh | Built-in camera: No | VESA mounting: Yes | Touchscreen: No | Weight (without stand): 3.9 kg | HDMI version: 2.0 | Display diagonal (metric): 68.6 cm | Energy efficiency class (HDR): G | Screen shape: Flat | Quick start guide: Yes | Swivel angle range: -45 - 45° | Energy efficiency class (SDR): E | Contrast ratio (typical): 1200:1 | RMS rated power: 4 W | NVIDIA G-SYNC: Yes | Haze rate: 25% | Height (without stand): 408.5 mm | Energy consumption (SDR) per 1000 hours: 21 kWh | Depth (with stand): 213 mm | Cables included: USB | Number of OSD languages: 12 | DisplayPort version: 1.4 | Cables included: HDMI | Height (with stand): 554 mm | Viewable size, vertical: 33.6 cm | Cables included: DisplayPort | Package weight: 8.2 kg | Number of speakers: 2 | Cables included: AC | Swivelling: Yes | Viewing angle, vertical: 178° | Pivot: Yes | USB Type-C downstream ports quantity: 2 | Contrast ratio (dynamic): 80000000:1 | Power consumption (typical): 21 W | Pixel pitch: 0.233 x 0.233 mm | AC input voltage: 100 - 240 V | Tilt adjustment: Yes | Power consumption (standby): 0.5 W | USB Type-A downstream ports quantity: 2 | Display number of colours: 1.07 billion colours | Viewing angle, horizontal: 178° | Horizontal scan range: 30 - 320 kHz | Panel mounting interface: 100 x 100 mm | Built-in USB hub: Yes | Weight (with stand): 5.7 kg | Adjustable height (max): 15 cm | Cable lock slot type: Kensington | Warnings: Avoid direct contact with liquids. | Number of downstream ports: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950