

Asustor AS1202T NAS/storage server Tower Realtek 1 GB DDR4 0 TB ADM Black



Model: AS1202T

Manufacturer: ASUSTOR

EAN: 4710474831937

Product Code: 299626

R3,812

Access Control List (ACL): Yes | System log: Yes | iSCSI support: Yes | Bad block scan: Yes | Online RAID migration: Yes | Total installed storage capacity: 0 TB | Operating system version: 5.0 | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 2500 Mbit/s | RAID support: Yes | Ethernet LAN data rates: 1000 Mbit/s | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | AC input voltage: 100 - 240 V | LED indicators: Yes | Security algorithms: 256-bit AES | Web-based management: Yes | Security algorithms: HTTPS | Product colour: Black | Security algorithms: SSH | Security algorithms: SNMP | Operating relative humidity (H-H): 5 - 95% | Supported file systems: ext3 | Cooling type: Active | Internal memory type: DDR4 | USB port: Yes | Server operating systems supported: Windows Server 2022 | Flash memory: 8000 MB | Storage drives installed: No | Server

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

operating systems supported: Windows Server 2012 | Power consumption (typical): 11.6 W | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Height: 165 mm | Supported file systems: ext4 | Type: NAS | Server operating systems supported: Windows Server 2019 | Device class: Home & Home Office | RAID levels: JBOD | Processor cores: 4 | Chassis type: Tower | Server operating systems supported: Windows Server 2016 | RAID levels: 1 | Ethernet LAN: Yes | Fan diameter: 7 cm | Operating system installed: ADM | Processor manufacturer: Realtek | Power supply unit (PSU) capacity: 65 W | Number of storage drives supported: 2 | Number of users: 4096 user(s) | DHCP server: Yes | Server operating systems supported: Windows Server 2008 R2 | Browser supported: FireFox, Chrome, Safari, Microsoft Edge | Processor family: Realtek | RAID levels: 0 | Supported file systems: HFS+ | Noise level: 18.6 dB | Storage drive sizes supported: 3.5" | Server operating systems supported: Windows Server 2003 | Processor frequency: 1.7 GHz | Linux operating systems supported: Yes | Width: 102 mm | Storage temperature (T-T): -20 - 70 °C | Ethernet LAN (RJ-45) ports: 1 | Windows operating systems supported: Windows 11 | Backup function: Yes | Weight: 1.14 kg | Windows operating systems supported: Windows 10 | Supported file systems: NTFS | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | Snapshot: Yes | Storage drive interface: Serial ATA | Installed storage drive type: No | Operating temperature (T-T): 0 - 40 °C | Supported network protocols: Supported), TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP, Syslog | S.M.A.R.T. support: Yes | Depth: 218 mm | Internal memory: 1 GB | Supported file systems: exFAT | Supported file systems: FAT32

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950