

Asustor AS1204T NAS Tower Realtek RTD1619B 1 GB DDR4 0 TB ADM Black



Model: AS1204T

Manufacturer: ASUSTOR

EAN: 4710474831944

Product Code: 299627

R5,125

Supported file systems: HFS+ | Supported file systems: FAT32 | Online RAID migration: Yes |
Supported file systems: exFAT | Supported file systems: ext4 | Supported file systems: ext3 |
Supported file systems: NTFS | System log: Yes | Device class: Home & Home Office | iSCSI support:
Yes | Bad block scan: Yes | Operating system version: 5.0 | Access Control List (ACL): Yes | Total
installed storage capacity: 0 TB | Web-based management: Yes | Ethernet LAN data rates: 100 |
Product colour: Black | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD |
Ethernet LAN data rates: 1000 Mbit/s | Processor model: RTD1619B | Storage temperature (T-T): -20
- 70 °C | Windows operating systems supported: Windows 10 | Height: 165 mm | Windows operating
systems supported: Windows 11 | Ethernet LAN: Yes | Supported network protocols: Supported),
TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP, Syslog | S.M.A.R.T.
support: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | Internal memory: 1 GB | Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

LAN data rates: 2500 Mbit/s | LED indicators: Yes | Storage drives installed: No | Number of users: 4096 user(s) | Backup function: Yes | Processor cores: 4 | Weight: 1.57 kg | Processor manufacturer: Realtek | Power consumption (typical): 22.8 W | Depth: 218 mm | Operating relative humidity (H-H): 5 - 95% | Processor family: Realtek | Snapshot: Yes | Noise level: 19.7 dB | Width: 164 mm | AC input voltage: 100 - 240 V | RAID levels: 0 | Operating system installed: ADM | Storage drive sizes supported: 3.5" | Fan diameter: 12 cm | Processor frequency: 1.7 GHz | Flash memory: 8000 MB | Security algorithms: HTTPS | DHCP server: Yes | Power supply unit (PSU) capacity: 65 W | Security algorithms: SSH | Server operating systems supported: Windows Server 2012 | Linux operating systems supported: Yes | RAID levels: JBOD | Server operating systems supported: Windows Server 2008 R2 | Browser supported: FireFox, Chrome, Safari, Microsoft Edge | RAID levels: 1 | Number of storage drives supported: 4 | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Cooling type: Active | Chassis type: Tower | Type: NAS | Server operating systems supported: Windows Server 2019 | Installed storage drive type: No | Internal memory type: DDR4 | USB port: Yes | Server operating systems supported: Windows Server 2022 | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: SNMP | Storage drive interface: Serial ATA | RAID support: Yes | Server operating systems supported: Windows Server 2003 | Operating temperature (T-T): 0 - 40 °C | Security algorithms: 256-bit AES | Server operating systems supported: Windows Server 2016

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950