

TP-Link Archer 5G AX3000 Wireless Dual- Band Gigabit Router



Model: Archer NX500

Manufacturer: TP-LINK

EAN: 1210002601610

Product Code: 299667

R6,625

Compliance certificates: RoHS | Compliance certificates: CE | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Windows operating systems supported: Windows XP Professional x64 | Security algorithms: WPA2-PSK | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows Vista x64 | Filtering: Yes | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 10 Pro x64 | Windows operating

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

systems supported: Windows 8 Enterprise | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Product colour: White | AC adapter included: Yes | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA | Power source type: AC | AC input frequency: 50/60 Hz | Ethernet LAN (RJ-45) ports: 2 | DHCP client: Yes | Security algorithms: 128-bit WEP | Package type: Box | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Windows operating systems supported: Windows 2000 Professional | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home x64 | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows 10 Education | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 10 Enterprise x64 | Reset button: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows RT 8.1 | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 10 | Antenna connector

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

type: SMA | Built-in display: No | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 100 | SIM card type: NanoSIM | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | Ethernet LAN interface type: Gigabit Ethernet | DMZ support: Yes | Guest access: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | 3G standards: DC-HSDPA | Mobile network generation: 5G | Cabling technology: 10/100/1000Base-T(X) | Wi-Fi standards: Wi-Fi 4 (802.11n) | 5G bands supported: 2600 | 5G bands supported: 800 | 5G bands supported: 900 | WLAN data transfer rate (max): 3000 Mbit/s | Product type: Desktop/pole router | Height: 190 mm | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Port forwarding: Yes | 4G bands supported: 900 | SIM card slot: Yes | Cables included: LAN (RJ-45) | WPS push button: Yes | IP address filtering: Yes | Number of guest networks (5 GHz): 1 | Port triggering: Yes | Ethernet LAN: Yes | 3G standards: HSPA | 3G standards: UMTS | 3G bands supported: 850 | 3G bands supported: 2100 MHz | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | Output voltage: 12 V | 5G bands supported: 3500 | URL filtering: Yes | Output current: 2 A | Maximum Tx power (5 GHz): 30 dBmW | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 3700 MHz | 4G bands supported: 3500 | 5G bands supported: 2500 | Number of guest networks (2.4 GHz): 1 | Quick installation guide: Yes | 5G bands supported: 700 | 5G bands supported: 1800 | 5G bands supported: 2300 | Mac operating systems supported: Yes | DSL WAN: No | 5G bands supported: 850 | Mac compatibility: Yes | Universal Plug and Play (UPnP): Yes | Antenna design: Internal & external | 5G bands supported: 3700 MHz | DHCP server: Yes | 3G bands supported: 900 | Wi-Fi standards: 802.11b | Parental control: Yes | Supported network protocols: IPv4, IPv6 | Dynamic DNS (DDNS): Yes | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | 4G bands supported: 1800 | 5G bands supported: 2100 | WLAN data transfer rate (first band): 574 Mbit/s | Wi-Fi standards: 802.11g | USB port: No | DoS attack prevention: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Antennas quantity: 10 | WLAN data transfer rate (second band): 2402 Mbit/s | 4G bands supported: 2100 | 4G bands supported: 800 | Depth: 99 mm | WAN connection type: RJ-45 | Ethernet WAN: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Linux operating systems supported: Yes | Width: 99 mm | Maximum Tx power (2.4 GHz): 20 dBmW

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950