

TP-Link TL- MR100- OUTDOOR wireless router Fast Ethernet Single-band (2.4 GHz) 4G White



Model: TL-MR100-Outdoor

Manufacturer: TP-LINK

EAN: 1210002601641

Product Code: 299668

R1,342

Receiver sensitivity: 11g 54M: -74 dBm 11n HT20: -73 dBm 11n HT40: -70 dBm | Certification: CE, RoHS | Reset button: Yes | Security algorithms: WPA | Security algorithms: WPA-PSK | DHCP client: Yes | 3G: Yes | Stateful Packet Inspection (SPI): Yes | Security algorithms: WPA2 | MAC address filtering: Yes | Operating temperature (T-T): -30 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11b | Ethernet LAN data rates: 100 | Power source type: DC, PoE | Product colour: White | Firmware upgradeable: Yes | DC-in jack: Yes | Guest access: Yes | 4G bands supported: 1800 | 4G: Yes | Output voltage: 12 V | On/off switch: Yes | USB port: No | Quick installation guide: Yes | 4G bands supported: 700 | Operating relative humidity (H-H): 10 - 90% |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cabling technology: 10/100Base-T(X) | Wi-Fi standards: Wi-Fi 4 (802.11n) | 4G bands supported: 2600 | 4G bands supported: 850 | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Supported network protocols: IPv4, IPv6 | DSL WAN: Yes | Depth: 100 mm | IP address filtering: Yes | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | SIM card slot: Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Ethernet LAN: Yes | DMZ support: Yes | DHCP server: Yes | Dynamic DNS (DDNS): Yes | Mounting kit: Yes | 4G standard: LTE-TDD & LTE-FDD | Port triggering: Yes | Storage temperature (T-T): -40 - 70 °C | 4G bands supported: 900 | Wall mountable: Yes | Universal Plug and Play (UPnP): Yes | Ethernet WAN: Yes | International Protection (IP) code: IP65 | Mobile network generation: 4G | Cables included: LAN (RJ-45) | Height: 54.7 mm | Ethernet LAN interface type: Fast Ethernet | Antennas quantity: 2 | Power over Ethernet (PoE): Yes | Port forwarding: Yes | Width: 226.6 mm | 3G standards: HSPA | 4G bands supported: 2100 | 4G bands supported: 800 | Output current: 1 A | 3G bands supported: 850 | 3G standards: UMTS | Power over Ethernet (PoE) voltage: 48 V | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 300 Mbit/s | Wi-Fi Multimedia (WMM)/(WME): Yes | WAN connection type: RJ-45 | 3G standards: HSPA+ | 3G/4G USB modem compatibility: No | 3G bands supported: 2100 MHz | 3G bands supported: 900 | Wi-Fi band: Single-band (2.4 GHz) | Firewall: Yes | Antenna design: External | Wireless statistics: Yes | PoE injector included: Yes | Wireless radio: Yes | Schedule access: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950