

HP Series 7 Pro 24 inch WUXGA USB-C Monitor - 724pu



Model: 8Y2F7AA

Manufacturer: HEWLETT-PACKARD

EAN: 197498467719

Product Code: 299824

R5,623

Bundled software: HP Display Center HP Client Management Script Library | Box contents: Monitor DisplayPort™ cable HDMI cable VESA Mount adapter Warranty card Quick Setup Poster 1 USB Type-C to Type-C cable AC power cord Color calibration report | Certification: Australian-New Zealand MEPS BIS BSMI CB CCC CE CECP CEL cTUVus EAC FCC GS Mark ISO 9241-307 KC KCC NOM PSB SEPA TUV-S VCCI Vietnam MEPS WEEE ISC Low blue light WW application UAE Ukraine EE Microsoft WHQL Certification (Windows 11 and Windows 10) Ukraine CoC Ukraine DOC | Manufacturer warranty: HP three-year limited warranty | LED backlight: Yes | Aspect ratio: 16:10 | Native aspect ratio: 16:10 | Tilt angle range: -5 - 20° | Display brightness (typical): 350 cd/m² | Product colour: Black | Power consumption (off): 0.3 W | Display resolution: 1920 x 1200 pixels | AC input frequency: 50/60 Hz | Display diagonal: 61 cm (24") | Cable lock slot: Yes | Width (with stand): 531.7 mm | Display surface: Matt | HDCP: Yes | DisplayPort version: 1.4 | AC input voltage: 100 - 240 V | Response time: 5 ms | DisplayPorts quantity: 1 | HD type: WUXGA | Depth (with stand): 195 mm | Height (with stand): 521.4 mm | Storage relative humidity (H-H): 20 - 80% | Screen shape: Flat | Power consumption (standby): 0.5 W | Quick start guide: Yes | Picture-in-Picture: Yes | HP segment: Business | Package width: 625

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

mm | Ethernet LAN: Yes | Package weight: 7.8 kg | Cables included: DisplayPort | Built-in camera: No | Tilt adjustment: Yes | Depth (without stand): 38.5 mm | Power supply type: Internal | Horizontal scan range: 30 - 75 kHz | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Package height: 415 mm | Power consumption (max): 160 W | Vertical scan range: 50 - 100 Hz | Supported graphics resolutions: 1280 x 1024 (SXGA) | Package type: Box | Supported graphics resolutions: 720 x 400 | UNSPSC-code: 43211902 | Weight: 5.2 kg | Swivel angle range: -45 - 45° | Low Blue Light technology: Yes | Cables included: HDMI | Height: 342.9 mm | Market positioning: Business | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | VESA mounting: Yes | Cables included: USB Type-C to USB Type-C | Width: 531.7 mm | Supported graphics resolutions: 1280 x 800 | Pixel density: 94 ppi | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Height (without stand): 342.9 mm | Power consumption (typical): 26.4 W | Built-in USB hub: Yes | Display diagonal (metric): 61 cm | Contrast ratio (dynamic): 10000000:1 | Cables included: AC | USB upstream port type: USB Type-B | Depth: 38.5 mm | Panel type: IPS | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) | Supported graphics resolutions: 1600 x 900 | Pivot: Yes | Stand included: Yes | Warranty card: Yes | Viewable size, horizontal: 51.8 cm | HDMI: Yes | Operating temperature (T-T): 5 - 35 °C | Viewing angle, horizontal: 178° | NVIDIA G-SYNC: No | AMD FreeSync: No | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Viewing angle, vertical: 178° | Display brightness: 350 cd/m² | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | On Screen Display (OSD): Yes | Pixel pitch: 0.27 x 0.27 mm | Feet colour: Silver | Operating relative humidity (H-H): 5 - 95% | Height adjustment: Yes | Package depth: 142 mm | Feet colour: Black | Width (without stand): 531.7 mm | Display brightness (peak): 350 cd/m² | Pivot angle: 0 - 90° | Anti-glare screen: Yes | Fast charging: Yes | USB Power Delivery (USB PD): Yes | HDMI version: 2.0 | Built-in speaker(s): No | Warnings: Unplug the monitor from the power source before cleaning. | USB Type-C DisplayPort Alternate Mode: Yes | Panel mounting interface: 100 x 100 mm | Remotely operated: Yes | Sustainability certificates: EPEAT | Swivelling: Yes | Viewable size, vertical: 32.4 cm | Ethernet LAN (RJ-45) ports: 1 | Weight (with stand): 5.2 kg | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Colour gamut: 99% | Display number of colours: 16.7 million colours | Touchscreen: No | sRGB coverage (typical): 99% | USB upstream port type: USB Type-A | Backlight type: Edge LED | Response time measurement type: GTG (Gray to Gray) | Contrast ratio (typical): 1500:1 | USB Type-A downstream ports quantity: 4 | Colour depth: 8 bit | Display technology: LCD | Detachable stand: Yes | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | HDMI ports quantity: 1 | Energy efficiency scale: A to G | Maximum

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

refresh rate: 100 Hz | General Product Safety Regulation (GPSR) URL: <https://support.hp.com/gb-en/product/setup-user-guides/hp-deskjet-2700-all-in-one-printer-series/model/31598160?sku=5AR83B&serialnumber=5AR83B> | HP GTIN (EAN/UPC): 888182569252, 888182569351 | Energy efficiency class (HDR): Not available | Number of USB Type-B upstream ports quantity: 1 | Energy consumption (SDR) per 1000 hours: 19.2 kWh | Energy efficiency class (SDR): E | Colour gamut standard: sRGB | Total carbon emissions, w/o use phase (kg of CO2e): 4 | Carbon emissions, logistics (kg of CO2e): 2 | Carbon emissions, manufacturing (kg of CO2e): 30 | Colour gamut standard: Rec. 709 | Colour gamut standard: DCI-P3 | Carbon emissions, end-of-life (kg of CO2e): 2 | Compliance certificates: CB | Compliance certificates: EAC | Compliance certificates: CE | Compliance certificates: GS mark | Compliance certificates: BSMI | Compliance certificates: CECP | Compliance certificates: BIS | Compliance certificates: CCC | European Product Registry for Energy Labelling (EPREL) code: 1887611 | Compliance certificates: Federal Communications Commission (FCC) | Total carbon footprint (kg of CO2e): 40 | USB Power Delivery up to: 100 W | Display bezel technology: Micro-Edge | Haze rate: 25% | Surface hardness: 3H | VESA Adaptive Sync support: Yes | Adjustable height (max): 15 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950