

Mercusys MB118-4G wireless router Fast Ethernet Single-band (2.4 GHz) White



Model: MB118-4G

Manufacturer: MERCUSYS

EAN: 6957939002848

Product Code: 299973

R1,306

4G standard: LTE-TDD & LTE-FDD | Firewall: Yes | 3G bands supported: 900 | 3G standards: HSPA+ | 3G standards: UMTS | 3G bands supported: 850 | Dynamic DNS (DDNS): Yes | 3G bands supported: 2100 MHz | DMZ support: Yes | Parental control: Yes | Antenna included: Yes | Mobile network generation: 4G | 3G/4G USB modem compatibility: No | 4G bands supported: 900 | Operating relative humidity (H-H): 10 - 90% | DSL WAN: No | Operating temperature (T-T): -30 - 60 °C | Power source type: DC, PoE | PoE injector included: Yes | WAN connection type: RJ-45 | 4G bands supported: 700 | Universal Plug and Play (UPnP): Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | DHCP server: Yes | Detachable antenna(s): Yes | Mounting kit: Yes | Number of simultaneously connected devices (max): 32 | 4G bands supported: 2100 | 4G bands supported: 800 | Wall mountable: Yes | 4G bands supported: 2600 | 4G bands supported: 850 | Height: 230.9 mm | Product type: Portable router |

Reset button: Yes | Ethernet LAN (RJ-45) ports: 1 | Number of products included: 1 pc(s) | Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

LAN interface type: Fast Ethernet | International Protection (IP) code: IP65 | Compliance certificates: RoHS | Compliance certificates: CE | Wi-Fi band: Single-band (2.4 GHz) | Quick installation guide: Yes | WLAN data transfer rate (max): 300 Mbit/s | SIM card slot: Yes | SIM card type: NanoSIM | 4G bands supported: 1800 | Antennas quantity: 4 | Cables included: LAN (RJ-45) | Wi-Fi standards: 802.11g | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | LED indicators: LAN, Power, WLAN | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11b | Power over Ethernet (PoE): Yes | Security algorithms: WPA2-PSK | Storage temperature (T-T): -40 - 70 °C | Port triggering: Yes | Ethernet WAN: Yes | Package type: Box | Ethernet LAN: Yes | Depth: 54.7 mm | AC adapter included: Yes | Width: 97.2 mm | 4G LTE category: 4 | USB port: No | Antenna design: Internal & external | Web-based management: Yes | Networking standards: IEEE 802.3at | Ethernet LAN data rates: 100 | Filtering: Yes | Networking standards: IEEE 802.3af | Network address translation (NAT): Yes | DHCP client: Yes | Product colour: White | Ethernet LAN data rates: 10 | DC-in jack: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950