

**Philips 1000
series
24E1N1300AE/00
computer
monitor 60.5 cm
(23.8) 1920 x
1080 pixels Full
HD LCD Black**



Model: 24E1N1300AE/00

Manufacturer: PHILIPS

EAN: 8712581804268

Product Code: 299974

R2,593

Exterior finish type: Textured | Regulatory Approvals: CB CE Mark TUV/ISO9241-307 TUV-BAUART
EAC FCC ICES-003 VCCI | USB Power Delivery up to: 65 W | Anti-glare screen: Yes | VESA mounting:
Yes | Component video sync: Separate Sync | Backlight type: W-LED | On Screen Display (OSD): Yes |
VESA Adaptive Sync support: Yes | USB Type-A downstream ports quantity: 2 | Height adjustment:
Yes | LowBlue mode: Yes | Power supply type: Internal | Low Blue Light technology: Yes | HDMI
version: 1.4 | Dynamic contrast ratio marketing name: Mega Infinity DCR | Number of speakers: 2 |
Doesn't contain: Mercury | Pixel density: 92.56 ppi | Height (without stand): 316 mm | On Screen
Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Screen Display (OSD) languages: Korean | Built-in speaker(s): Yes | On Screen Display (OSD) languages: Simplified Chinese | On Screen Display (OSD) languages: Spanish | On Screen Display (OSD) languages: Japanese | Picture enhancement: SmartImage game | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Portuguese | Touchscreen: No | EasyRead mode: Yes | Power consumption (typical): 18.3 W | Display technology: LCD | Haze rate: 25% | Mean time between failures (MTBF): 50000 h | Built-in USB hub: Yes | USB Power Delivery (USB PD): Yes | Power consumption (standby): 0.5 W | HDMI ports quantity: 1 | DDC/CI: Yes | Depth (without stand): 45 mm | Display diagonal (metric): 60.5 cm | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | AMD FreeSync: No | Viewable size, vertical: 29.6 cm | Panel type: IPS | Surface hardness: 3H | Contrast ratio (typical): 1300:1 | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Built-in camera: No | Packaging recyclability rate: 100% | Tilt adjustment: Yes | Audio output: Yes | Maximum refresh rate: 100 Hz | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | On Screen Display (OSD) languages: Turkish | HDMI: Yes | On Screen Display (OSD) languages: English | Plug and Play: Yes | On Screen Display (OSD) languages: Ukrainian | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Greek | HDCP version: 1.4 | Doesn't contain: PVC/BFR | Weight (without stand): 3.06 kg | Non-operating altitude: 0 - 12192 m | Panel mounting interface: 100 x 100 mm | Energy efficiency class (SDR): E | Response time (fast): 1 ms | Width (without stand): 542 mm | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | Viewable size, horizontal: 52.7 cm | Stand included: Yes | Weight (with stand): 4.68 kg | Display sRGB: Yes | Response time: 4 ms | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | LED indicators: Operation | Native aspect ratio: 16:9 | Height (with stand): 442 mm | LED indicators: Stand-by | AC input voltage: 100 - 240 V | Depth (with stand): 187 mm | Display diagonal: 60.5 cm (23.8") | HDCP: Yes | NVIDIA G-SYNC: No | HD type: Full HD | Width (with stand): 542 mm | Product colour: Black | Screen shape: Flat | Display brightness (typical): 250 cd/m² | Power consumption (off): 0.3 W | Cable lock slot: Yes | Operating altitude: 0 - 3658 m | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 115 kHz | Package weight: 6.97 kg | Cable lock slot type: Kensington | Manual: Yes | Operating relative humidity (H-H): 20 - 80% | Package height: 391 mm | Vertical scan range: 48 - 100 Hz | Package depth: 141 mm | Cables included: USB Type-C | Viewing angle, horizontal: 178° | Storage temperature (T-T): -20 - 60 °C | Package width: 730 mm | Pixel pitch: 0.2745 x 0.2745 mm | Cables included: Power | Operating temperature (T-T): 0 - 40 °C | Cables included: HDMI | Display number of colours: 16.7 million colours | Tilt angle range: -5 - 20° | Response time measurement type: GTG (Gray to Gray) | European

Product Registry for Energy Labelling (EPREL) code: 1833270 | Adjustable height (max): 10 cm |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Response time (MPRT): 1 ms | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950