

AG Neovo SC-2203 computer monitor 55.9 cm (22) 1920 x 1080 pixels Full HD LCD Black



Model: SC-2203

Manufacturer: AG NEOVO

EAN: 4710739598148

Product Code: 300102

R4,048

Operating temperature (T-T): 5 - 35 °C | Power consumption (typical): 16 W | Quick start guide: Yes | Native aspect ratio: 16:9 | Response time: 5 ms | Built-in USB hub: No | Power consumption (off): 0.3 W | Product colour: Black | Height (with stand): 373.8 mm | Compliance certificates: WEEE | HD type: Full HD | VESA mounting: Yes | Tilt angle range: -5 - 15° | Package width: 555 mm | Digital vertical frequency: 48 - 75 Hz | Compliance certificates: RoHS | Compliance certificates: CE | Display number of colours: 1.07 billion colours | Compliance certificates: UKCA | Cable lock slot: Yes | Contrast ratio (typical): 20000000:1 | European Product Registry for Energy Labelling (EPREL) code: 1949709 | HDMI ports quantity: 1 | VGA (D-Sub) ports quantity: 1 | Warnings: Do not place heavy objects on the monitor to avoid damage. | Package height: 373 mm | Package depth: 110 mm | Pixel pitch: 0,241 x 0,241 mm | Package weight: 3.6 kg | Display resolution: 1920 x 1080 pixels | Cables included: AC |

Compliance certificates: REACH | Storage temperature (T-T): -20 - 60 °C | Compliance certificates:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Low Voltage Directive (LVD) | Power consumption (standby): 0.5 W | Compliance certificates: EAC | Depth (with stand): 167,4 mm | Touchscreen: No | Display diagonal: 21.45" | Operating relative humidity (H-H): 20 - 85% | Digital horizontal frequency: 30 - 85 kHz | Warnings: Do not open the monitor case to prevent electric shock. | Warnings: Avoid prolonged staring at the screen at high brightness to prevent eye fatigue. | Display brightness (typical): 280 cd/m² | Tilt adjustment: Yes | Viewing angle, vertical: 178° | Height adjustment: No | HDMI version: 1.4 | Screen shape: Flat | Cables included: HDMI | Viewing angle, horizontal: 178° | Market positioning: Business | Storage relative humidity (H-H): 10 - 90% | Panel mounting interface: 100 x 100 mm | Display technology: LCD | Width (with stand): 491,8 mm | Cable lock slot type: Kensington | RMS rated power: Not applicable | Weight (with stand): 2.6 kg | Built-in speaker(s): No | Headphone out: No | Number of speakers: Not applicable | Height (without stand): 289.5 mm | BNC input ports: 1 | BNC output ports: 1 | Width (without stand): 491,8 mm | Energy efficiency scale: A to G | Panel type: VA | Built-in camera: No | Weight (without stand): 2.3 kg | Depth (without stand): 44.9 mm | HDMI: Yes | Sustainability certificates: EAC | Sustainability certificates: CE | Sustainability certificates: Low Voltage Directive (LVD) | Sustainability certificates: REACH | Energy consumption (SDR) per 1000 hours: 16 kWh | Energy efficiency class (HDR): Not available | Sustainability compliance: Yes | Sustainability certificates: WEEE | Sustainability certificates: UKCA | Sustainability certificates: RoHS | Energy efficiency class (SDR): E

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950