

Keenetic Hero 4G+ (KN-2312) AX3000 Mesh Wi-Fi 6 4G+ Modem Router with 2 SIM Slots, a 5-Port Gigabit Smart Switch and USB 3.0 Port



Model: KN-2312-01-EU

Manufacturer: KEENETIC

EAN: 4897082922025

Product Code: 300156

R3,361

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | WPS push button: Yes | Built-in FTP server: Yes | Cloud-managed: Yes | Policy-based routing: Yes | Dynamic DNS (DDNS): Yes | IPv4 & IPv6 features: IPv6 SSH | 4G bands supported: 850 |

4G bands supported: 2500 | SIM card type: NanoSIM | 4G bands supported: 800 | 4G bands

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: 900 | IPv4 & IPv6 features: IPv6 Telnet | Traffic statistics: Yes | 4G bands supported: 2300 | Command-line interface (CLI): Yes | Guest access: Yes | DoS attack prevention: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | 4G bands supported: 1800 | 3G bands supported: 850 | 3G bands supported: 900 | Firewall: Yes | 3G/4G USB modem compatibility: Yes | Antenna design: External | Parental control: Yes | Web-based setup wizard: Yes | Mobile network generation: 4G | WLAN data transfer rate (first band): 574 Mbit/s | Captive portal: Yes | 3G bands supported: 2100 MHz | PPPoE/PPTP/L2TP pass-through: Yes | Schedule access: Yes | Support Samba (storage): Yes | MU-MIMO technology: Yes | WLAN data transfer rate (second band): 2402 Mbit/s | Number of data streams: 2x2 | Media server: Yes | IntelliQoS: Yes | Intelligent Mesh technology: Yes | 4G data rate (max): 300 Mbit/s | VPN server: OpenVPN | Bandwidth control: Yes | Ping check: Yes | L2TP/PPTP data rate: 800 Mbit/s | IPoE/PPPoE data rate: 1800 Mbit/s | USSD request support: Yes | WireGuard throughput: 460 Mbit/s | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Routing table: DHCP | Internet connection backup: Yes | WAN connection type: RJ-45, WISP | Ethernet WAN: Yes | Antenna connector type: SMA | System event log: Yes | 3G standards: HSDPA | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Ethernet LAN: Yes | SIM card slot: Yes | Firewall security: SPI | Quick start guide: Yes | 3G: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Width: 217 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Antennas quantity: 4 | IGMP snooping: Yes | Weight: 600 g | Ethernet LAN (RJ-45) ports: 5 | Cabling technology: 10/100/1000Base-T(X) | Operating temperature (T-T): 0 - 40 °C | Backup function: Yes | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | Modulation: OFDMA | Security algorithms: WPA-PSK | Security algorithms: OWE | Detachable antenna(s): Yes | Built-in processor: Yes | WLAN data transfer rate (max): 3000 Mbit/s | Power source type: AC | Security algorithms: WPA2-Enterprise | Security algorithms: WPA2-PSK | Depth: 159 mm | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Product type: Tabletop router | Flash memory: 256 MB | Mobile operating systems supported: Android | DHCP server: Yes | Ethernet LAN interface type: Gigabit Ethernet | Quality of Service (QoS) support: Yes | 3G standards: HSUPA | Operating relative humidity (H-H): 20 - 95% | Universal Plug and Play (UPnP): Yes | Processor frequency: 1300 MHz | 3G standards: WCDMA | Mobile operating systems supported: iOS | Output voltage: 12 V | Short Message Service (SMS): Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Port forwarding: Yes | Security algorithms: WPA3-PSK | 4G bands supported: 2100 | 4G bands supported: 2600 | Cables included: LAN (RJ-45) | Height: 45 mm | Antenna gain level (max): 4 dBi | Output current: 2 A | Internal memory: 512 MB | Security algorithms: WEP | Security algorithms: WPA3-Enterprise | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | AC adapter included: Yes | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Processor manufacturer: MediaTek | Wi-Fi Multimedia (WMM)/(WME): Yes | USB port:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Internal memory type: DDR3 | Web-based management: Yes | MAC address filtering: Yes | DHCP client: Yes | Product colour: White | Network address translation (NAT): Yes | MIMO: Yes | Ethernet LAN data rates: 1000 Mbit/s | Product colour: Grey | DC-in jack: Yes | Ethernet LAN data rates: 100 | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | AC input frequency: 50/60 Hz | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11h | Networking standards: IEEE 802.11v | Networking standards: IEEE 802.11r | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11b | HTTPS security for access via KeenDNS: Yes | WireGuard: Yes | Modem chipset: ASR1826 | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | Cloudflare DNS: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950