

Keenetic Starter (KN-1121) N300 Mesh Wi-Fi Router with a 3- Port Smart Switch



Model: KN-1121-01-EU

Manufacturer: KEENETIC

EAN: 4897082922292

Product Code: 300160

R677

Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Internal memory: 128 MB | Backup function: Yes | Firewall security: SPI | Captive portal: Yes | USB port: No | Wi-Fi standards: Wi-Fi 4 (802.11n) | Antennas quantity: 2 | Number of guest networks (2.4 GHz): 7 | Number of users: 75 user(s) | IPv4 & IPv6 features: IPv6 Telnet | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | WLAN data transfer rate (first band): 300 Mbit/s | Antenna design: External | Height: 26 mm | Product type: Tabletop router | Universal Plug and Play (UPnP): Yes | Wi-Fi band: Single-band (2.4 GHz) | Mobile operating systems supported: Android | DHCP server: Yes | Dynamic DNS (DDNS): Yes | Parental control: Yes | Firewall: Yes | Cloud-managed: Yes | Flash memory: 32 MB | Mobile operating systems supported: iOS | WPS push button: Yes | Number of guest networks (5 GHz): 7 | Traffic statistics: Yes | Schedule access: Yes | IGMP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

snooping: Yes | Width: 107 mm | WLAN data transfer rate (max): 300 Mbit/s | Cabling technology: 10/100Base-T(X) | System event log: Yes | WAN connection type: RJ-45, WISP | Output voltage: 5 V | Depth: 91 mm | Guest access: Yes | Command-line interface (CLI): Yes | Web-based setup wizard: Yes | Processor manufacturer: MediaTek | Ethernet LAN: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | DoS attack prevention: Yes | Number of products included: 1 pc(s) | Port forwarding: Yes | Ethernet LAN interface type: Fast Ethernet | Intelligent Mesh technology: Yes | IPv4 & IPv6 features: IPv6 SSH | Built-in processor: Yes | Policy-based routing: Yes | VPN server: OpenVPN | Bandwidth control: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Cloudflare DNS: Yes | IPoE/PPPoE data rate: 95 Mbit/s | Internet connection backup: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | L2TP/PPTP data rate: 95 Mbit/s | USSD request support: Yes | IntelliQoS: Yes | Routing table: DHCP | Output current: 1 A | HTTPS security for access via KeenDNS: Yes | WireGuard throughput: 45 Mbit/s | WireGuard: Yes | PPPoE/PPTP/L2TP pass-through: Yes | Ping check: Yes | Product colour: Grey | Product colour: White | DHCP client: Yes | Networking standards: IEEE 802.11k | Security algorithms: WPA2-Enterprise | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: OWE | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11a | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11v | DC-in jack: Yes | Security algorithms: WPA3-Enterprise | Stateful Packet Inspection (SPI): Yes | LED indicators: LAN, Power, WLAN | Network address translation (NAT): Yes | AC input voltage: 100 - 240 V | Processor frequency: 575 MHz | Quick start guide: Yes | Weight: 113 g | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Ethernet LAN data rates: 100 | AC input frequency: 50/60 Hz | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Cables included: LAN (RJ-45) | Operating temperature (T-T): 0 - 40 °C | Processor model: MediaTek MT7628N | Internal memory type: DDR2 | Ethernet LAN (RJ-45) ports: 3 | Ethernet WAN: Yes | AC adapter included: Yes | Power source type: AC | Quality of Service (QoS) support: Yes | Quick installation guide: Yes | Operating relative humidity (H-H): 20 - 95%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950