

Keenetic Titan (KN-1812) BE7200 Mesh Wi-Fi 7 Multi- Gigabit Router with a 110G, 12.5G and 41G Smart Switch, Multifunctional USB 3.2 and 2.0 Ports



Model: KN-1812-01-EU

Manufacturer: KEENETIC

EAN: 4897082922537

Product Code: 300162

R4,764

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | IntelliQoS: Yes | USSD request

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

support: Yes | Cloudflare DNS: Yes | HTTPS security for access via KeenDNS: Yes | Direct or cloud access via KeenDNS: Yes | WireGuard: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | WPS push button: Yes | Built-in FTP server: Yes | Cloud-managed: Yes | Universal Plug and Play (UPnP): Yes | Number of guest networks (5 GHz): 7 | System event log: Yes | Product type: Tabletop router | USB port: Yes | Number of guest networks (2.4 GHz): 7 | Support Samba (storage): Yes | Antenna design: External | Output current: 3 A | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | IGMP snooping: Yes | Backup function: Yes | Guest access: Yes | Traffic statistics: Yes | Schedule access: Yes | Internal memory: 1024 MB | Number of data streams: 4x4 | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | SIM card slot: No | Mobile operating systems supported: iOS | Command-line interface (CLI): Yes | Firewall: Yes | MU-MIMO technology: Yes | Web-based setup wizard: Yes | WLAN data transfer rate (second band): 5764 Mbit/s | Height: 45 mm | WLAN data transfer rate (first band): 300 Mbit/s | Parental control: Yes | Number of users: 512 user(s) | Bandwidth control: Yes | Flash memory: 256 MB | Mobile operating systems supported: Android | DHCP server: Yes | Captive portal: Yes | 3G/4G USB modem compatibility: Yes | VPN server: OpenVPN | Intelligent Mesh technology: Yes | Routing table: DHCP | Housing material: Plastic | Firewall security: SPI | WAN connection type: RJ-45, WISP | Policy-based routing: Yes | DoS attack prevention: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Wi-Fi Multimedia (WMM)/(WME): Yes | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | Routing table: Manual | Ping check: Yes | Media server: Yes | IPv4 & IPv6 features: IPv6 Telnet | Built-in processor: Yes | L2TP/PPTP data rate: 3000 Mbit/s | PPPoE/PPTP/L2TP pass-through: Yes | WireGuard throughput: 900 Mbit/s | Internet connection backup: Yes | IPoE/PPPoE data rate: 10000 Mbit/s | Ethernet LAN interface type: 10 Gigabit Ethernet | MIMO: Yes | Quality of Service (QoS) support: Yes | Product colour: White | AC adapter included: Yes | Cabling technology: 10/100/1000/2500/5000/10000Base-T | Modulation: OFDMA | Networking standards: IEEE 802.11v | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.11k | WLAN data transfer rate (max): 7200 Mbit/s | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | DHCP client: Yes | Ethernet LAN (RJ-45) ports: 6 | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Cables included: LAN (RJ-45) | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Weight: 735 g | USB 2.0 ports quantity: 1 | AC input frequency: 50/60 Hz | Processor frequency: 1800 MHz | Wi-Fi standards: Wi-Fi 4 (802.11n) | Quick start guide: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Internal memory type: DDR4 | Ethernet LAN data rates: 1000 Mbit/s | LED indicators: LAN, Power, WLAN | Antennas quantity: 4 | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Ethernet LAN data rates: 2500 Mbit/s | Ethernet LAN data

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

rates: 100 | DC-in jack: Yes | Security algorithms: WPA3-Enterprise | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Width: 217 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 7 (802.11be) | Processor manufacturer: MediaTek | Ethernet WAN: Yes | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 10000 Mbit/s | Security algorithms: WPA-PSK | AC input voltage: 100 - 240 V | Reset button: Yes | Security algorithms: OWE | Output voltage: 12 V | Depth: 159 mm | Ethernet LAN: Yes | Operating relative humidity (H-H): 20 - 95% | Processor cores: 3 | Top Wi-Fi standard: Wi-Fi 7 (802.11be) | Network address translation (NAT): Yes | Power source type: AC | Processor model: MediaTek MT7988D

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950