

Keenetic Skipper (KN- 1912) AC1200 Mesh Wi-Fi 5 Router with a 4- Port Gigabit Smart Switch and USB Port



Model: KN-1912-01-EU

Manufacturer: KEENETIC

EAN: 4897082921103

Product Code: 300163

R1,235

Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | DHCP client: Yes | Ethernet LAN data rates: 100 | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Weight: 270 g | Processor model: EcoNet EN7528DU | Output voltage: 12 V | LED indicators: LAN, Power, WAN | Ethernet LAN (RJ-45) ports: 4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Processor cores: 2 | Product colour: Grey | Antennas quantity: 4 | Operating temperature (T-T): 0 - 40 °C | AC input frequency: 50/60 Hz | Quick installation guide: Yes | Ethernet LAN interface type: Gigabit Ethernet | Processor manufacturer:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

MediaTek | USB 2.0 ports quantity: 1 | Operating relative humidity (H-H): 20 - 95% | MIMO: Yes | Quality of Service (QoS) support: Yes | Quick start guide: Yes | Product colour: White | AC adapter included: Yes | DC-in jack: Yes | Ethernet LAN data rates: 1000 Mbit/s | Processor frequency: 900 MHz | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Cables included: LAN (RJ-45) | AC input voltage: 100 - 240 V | Power source type: AC | Internal memory type: DDR3 | Network address translation (NAT): Yes | Networking standards: IEEE 802.1Q | Security algorithms: WPA-PSK | Ethernet WAN: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Networking standards: IEEE 802.11v | Security algorithms: WPA2-Enterprise | Security algorithms: OWE | Networking standards: IEEE 802.11k | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | WLAN data transfer rate (max): 1200 Mbit/s | PPPoE/PPTP/L2TP pass-through: Yes | IntelliQoS: Yes | Routing table: DHCP | USSD request support: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | HTTPS security for access via KeenDNS: Yes | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | Cloudflare DNS: Yes | WireGuard: Yes | Number of data streams: 2x2 | MU-MIMO technology: Yes | Bandwidth control: Yes | Antenna design: External | Number of guest networks (5 GHz): 7 | Support Samba (storage): Yes | Number of guest networks (2.4 GHz): 7 | Intelligent Mesh technology: Yes | Schedule access: Yes | VPN server: OpenVPN | Media server: Yes | USB port: No | Web-based setup wizard: Yes | WPS push button: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Universal Plug and Play (UPnP): Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Mobile operating systems supported: Android | DHCP server: Yes | Number of users: 199 user(s) | WLAN data transfer rate (second band): 867 Mbit/s | Internal memory: 256 MB | WAN connection type: RJ-45, WISP | Firewall security: SPI | Guest access: Yes | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | Cabling technology: 10/100/1000Base-T(X) | Parental control: Yes | Firewall: Yes | System event log: Yes | Mobile operating systems supported: iOS | Flash memory: 128 MB | Port forwarding: Yes | Built-in FTP server: Yes | Cloud-managed: Yes | Dynamic DNS (DDNS): Yes | Command-line interface (CLI): Yes | DoS attack prevention: Yes | Number of products included: 1 pc(s) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G/4G USB modem compatibility: Yes | Captive portal: Yes | Output current: 1.5 A | Wi-Fi Multimedia (WMM)/(WME): Yes | Built-in processor: Yes | IPv4 & IPv6 features: IPv6 Telnet | Height: 29 mm | Product type: Tabletop router | Ethernet LAN: Yes | SIM card slot: No | Depth: 110 mm | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Policy-based routing: Yes | Backup function: Yes | IGMP snooping: Yes | Traffic statistics: Yes | Width: 159 mm | Internet connection backup: Yes | Ping check: Yes | IPoE/PPPoE data rate: 1800 Mbit/s | L2TP/PPTP data rate: 800 Mbit/s |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

WireGuard throughput: 130 Mbit/s

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950