

Keenetic Speedster (KN- 3013) AC1200 Mesh Wi-Fi 5 Gigabit Router/Extender with a 4-Port Gigabit Smart Switch



Model: KN-3013-01-EU

Manufacturer: KEENETIC

EAN: 4897082922407

Product Code: 300165

R1,114

Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Internet connection backup: Yes | IPoE/PPPoE data rate: 1800 Mbit/s | Number of guest networks (5 GHz): 7 | VPN server: OpenVPN | MU-MIMO technology: Yes | L2TP/PPTP data rate: 800 Mbit/s | PPPoE/PPTP/L2TP pass-through: Yes | Number of data streams: 2x2 | Antenna design: External | Ping check: Yes | Bandwidth control: Yes | WireGuard throughput: 180 Mbit/s | Number of

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

guest networks (2.4 GHz): 7 | Schedule access: Yes | Compliance certificates: CE | Intelligent Mesh technology: Yes | HTTPS security for access via KeenDNS: Yes | WireGuard: Yes | Cloudflare DNS: Yes | IntelliQoS: Yes | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | USSD request support: Yes | Routing table: DHCP | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11v | Web-based management: Yes | MAC address filtering: Yes | Firewall security: SPI | Networking standards: IEEE 802.11ac | Operating relative humidity (H-H): 20 - 95% | Depth: 110 mm | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Ethernet LAN: Yes | SIM card slot: No | DHCP client: Yes | Ethernet LAN (RJ-45) ports: 4 | AC input frequency: 50/60 Hz | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Flash memory: 128 MB | Port forwarding: Yes | Cabling technology: 10/100/1000Base-T(X) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Product colour: White | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | System event log: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11b | Product type: Tabletop router | DoS attack prevention: Yes | Ethernet LAN data rates: 1000 Mbit/s | IPv4 & IPv6 features: IPv6 SSH | USB port: No | LED indicators: Power | DC-in jack: Yes | Processor manufacturer: MediaTek | Internal memory type: DDR3 | MIMO: Yes | AC adapter included: Yes | Number of products included: 1 pc(s) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | IGMP snooping: Yes | Internal memory: 128 MB | Width: 159 mm | Backup function: Yes | Network address translation (NAT): Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Traffic statistics: Yes | Processor frequency: 880 MHz | Quick start guide: Yes | AC input voltage: 100 - 240 V | Processor cores: 2 | Antennas quantity: 4 | Weight: 264 g | Mobile operating systems supported: iOS | Policy-based routing: Yes | Number of users: 199 user(s) | WLAN data transfer rate (second band): 867 Mbit/s | Processor model: MediaTek MT7621DA | Command-line interface (CLI): Yes | Firewall: Yes | Web-based setup wizard: Yes | Output voltage: 12 V | Cables included: LAN (RJ-45) | Height: 29 mm | WLAN data transfer rate (first band): 300 Mbit/s | Ethernet LAN data rates: 100 | Universal Plug and Play (UPnP): Yes | Parental control: Yes | Networking standards: IEEE 802.11k | Cloud-managed: Yes | Guest access: Yes | Output current: 1 A | Mobile operating systems supported: Android | DHCP server: Yes | Captive portal: Yes | IPv4 & IPv6 features: IPv6 Telnet | 3G/4G USB modem compatibility: No | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Ethernet WAN: Yes | Power source type: AC | Security algorithms: WPA3-PSK | WAN connection type: RJ-45, WISP | WPS push button: Yes | Built-in processor: Yes | Security algorithms: WPA3-Enterprise | Security algorithms: WPA-PSK | Wi-Fi Multimedia (WMM)/(WME): Yes | WLAN data transfer rate (max): 1200 Mbit/s | External power adapter: Yes | Security algorithms: WPA2-Enterprise | Security

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

algorithms: WEP | Security algorithms: OWE | Housing material: Plastic

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950