

Keenetic Hopper DSL (KN-3610) AX1800 Mesh Wi-Fi 6 Supervectoring VDSL2/ADSL2+ Modem Router with a 4-Port Gigabit Smart Switch and USB 3.0 Port



Model: KN-3610-01EN

Manufacturer: KEENETIC

EAN: 4897082921356

Product Code: 300167

R2,361

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | Packaging content: DSL splitter | Bandwidth control: Yes | MU-MIMO technology: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Number of guest networks (2.4 GHz): 7 | Number of guest networks (5 GHz): 7 | Support Samba (storage): Yes | Intelligent Mesh technology: Yes | Schedule access: Yes | VPN server: OpenVPN | Internet connection backup: Yes | Media server: Yes | IPoE/PPPoE data rate: 1800 Mbit/s | WireGuard throughput: 180 Mbit/s | Antenna design: External | Number of data streams: 2x2 | Ping check: Yes | L2TP/PPTP data rate: 800 Mbit/s | AdGuard ad blocker: Yes | UDP-to-HTTP proxy: Yes | WireGuard: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Routing table: DHCP | PPPoE/PPTP/L2TP pass-through: Yes | IntelliQoS: Yes | HTTPS security for access via KeenDNS: Yes | Cloudflare DNS: Yes | USSD request support: Yes | DHCP client: Yes | Ethernet LAN (RJ-45) ports: 4 | Firmware upgradeable: Yes | Ethernet LAN data rates: 1000 Mbit/s | DC-in jack: Yes | Product colour: White | Network address translation (NAT): Yes | Product colour: Grey | MIMO: Yes | AC input voltage: 100 - 240 V | Modulation: OFDMA | Quick start guide: Yes | Weight: 445 g | Stateful Packet Inspection (SPI): Yes | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 100 | Processor frequency: 900 MHz | Power source type: AC | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.1Q | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11a | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11v | Security algorithms: WPA2-Enterprise | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Security algorithms: OWE | Internal memory: 256 MB | Quality of Service (QoS) support: Yes | AC adapter included: Yes | Processor manufacturer: MediaTek | Depth: 154 mm | Number of products included: 1 pc(s) | Output current: 1.5 A | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN: Yes | Processor model: EcoNet EN7516GT | Internal memory type: DDR3 | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN interface type: Gigabit Ethernet | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | WLAN data transfer rate (max): 1800 Mbit/s | Output voltage: 12 V | Housing material: Plastic | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Ethernet WAN: Yes | Built-in processor: Yes | Mobile operating systems supported: Android | Cables included: LAN (RJ-45) | Mobile operating systems supported: iOS | Operating relative humidity (H-H): 20 - 95% | Flash memory: 128 MB | Wi-Fi standards: Wi-Fi 4 (802.11n) | Processor cores: 2 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Width: 214 mm | Backup function: Yes | Height: 33 mm | Product type: Tabletop router | USB port: Yes | ADSL2: Yes | Traffic statistics: Yes | IGMP snooping: Yes | Guest access: Yes | Policy-based routing: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | DHCP server: Yes | Firewall security: SPI | RJ-11 ports quantity: 1 | 3G/4G USB modem compatibility: Yes | WLAN data transfer rate

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

(second band): 1201 Mbit/s | Number of users: 256 user(s) | Parental control: Yes | VDSL2: Yes | ADSL2+: Yes | Command-line interface (CLI): Yes | System event log: Yes | WLAN data transfer rate (first band): 300 Mbit/s | IPv4 & IPv6 features: IPv6 SSH | SIM card slot: No | Firewall: Yes | DoS attack prevention: Yes | DSL WAN: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | WAN connection type: RJ-45, WISP | IPv4 & IPv6 features: IPv6 Telnet | Built-in FTP server: Yes | Cloud-managed: Yes | Internal modem: Yes | WPS push button: Yes | Web-based setup wizard: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Universal Plug and Play (UPnP): Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Captive portal: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950