

Keenetic Sprinter SE (KN- 3712) AX3000 Mesh Wi-Fi 6 Gigabit Router/Extender with a 4-Port Gigabit Smart Switch



Model: KN-3712-01-EU

Manufacturer: KEENETIC

EAN: 4897082922216

Product Code: 300168

R2,056

Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Firewall: Yes | Operating temperature (T-T): 0 - 40 °C | Mobile operating systems supported: Android | DHCP server: Yes | Web-based management: Yes | Firewall security: SPI | Operating relative humidity (H-H): 20 - 95% | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Ethernet LAN: Yes | SIM card slot: No | DHCP client: Yes | Ethernet LAN (RJ-45) ports: 4 | AC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

input frequency: 50/60 Hz | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Flash memory: 128 MB | Port forwarding: Yes | Depth: 170 mm | WLAN data transfer rate (max): 3000 Mbit/s | Networking standards: IEEE 802.11a | Security algorithms: WPA3-Enterprise | Cloud-managed: Yes | Weight: 396 g | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Universal Plug and Play (UPnP): Yes | Number of guest networks (5 GHz): 7 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Built-in processor: Yes | Web-based setup wizard: Yes | DoS attack prevention: Yes | Number of products included: 1 pc(s) | Ethernet LAN data rates: 1000 Mbit/s | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | System event log: Yes | USB port: No | Processor manufacturer: MediaTek | Internal memory type: DDR4 | DC-in jack: Yes | LED indicators: LAN, Power, WLAN | WLAN data transfer rate (second band): 2402 Mbit/s | Security algorithms: WPA-PSK | Quick installation guide: Yes | Backup function: Yes | Guest access: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Traffic statistics: Yes | MIMO: Yes | Quality of Service (QoS) support: Yes | Product colour: White | AC adapter included: Yes | IGMP snooping: Yes | Quick start guide: Yes | AC input voltage: 100 - 240 V | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Mobile operating systems supported: iOS | Cabling technology: 10/100/1000Base-T(X) | Processor frequency: 1300 MHz | Antennas quantity: 5 | DDoS protection: Yes | Modulation: OFDMA | Command-line interface (CLI): Yes | Height: 42 mm | Product type: Tabletop router | Internal memory: 512 MB | Power source type: AC | MU-MIMO technology: Yes | Number of users: 256 user(s) | Parental control: Yes | Output voltage: 12 V | Width: 170 mm | Antenna design: Internal | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Cables included: LAN (RJ-45) | WLAN data transfer rate (first band): 300 Mbit/s | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.11v | VPN server: OpenVPN | Number of guest networks (2.4 GHz): 7 | Bandwidth control: Yes | Output current: 1 A | MAC address filtering: Yes | Security algorithms: WEP | Captive portal: Yes | IPv4 & IPv6 features: IPv6 Telnet | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Number of data streams: 3x3 | 3G/4G USB modem compatibility: No | Ethernet WAN: Yes | Intelligent Mesh technology: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Networking standards: IEEE 802.11ac | Security algorithms: OWE | Housing material: Plastic | WAN connection type: RJ-45, WISP | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | WPS push button: Yes | Network address translation (NAT): Yes | Security algorithms: WPA2-Enterprise | Policy-based routing: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Schedule access: Yes | Internet connection backup: Yes | IPoE/PPPoE data rate: 1800 Mbit/s | PPPoE/PPTP/L2TP pass-through: Yes | Ping check: Yes | WireGuard: Yes | IntelliQoS: Yes | L2TP/PPTP data rate: 900 Mbit/s | HTTPS security for access

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

via KeenDNS: Yes | WireGuard throughput: 460 Mbit/s | Routing table: DHCP | USSD request support: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Cloudflare DNS: Yes | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950