

Keenetic Hopper SE (KN-3812) AX3000 Mesh Wi-Fi 6 Gigabit Router with a 4- Port Gigabit Smart Switch and USB 3.0 Port



Model: KN-3812-01-EU

Manufacturer: KEENETIC

EAN: 4897082922230

Product Code: 300169

R2,269

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | IntelliQoS: Yes | Cloudflare DNS: Yes | WireGuard: Yes | Direct or cloud access via KeenDNS: Yes | HTTPS security for access via KeenDNS: Yes | USSD request support: Yes | AdGuard ad blocker: Yes | UDP-to-HTTP proxy: Yes | Cables included: LAN (RJ-45) | DC-in jack: Yes | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Product colour: White | AC adapter included:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Internal memory: 512 MB | Routing table: DHCP | Universal Plug and Play (UPnP): Yes | Depth: 170 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | MIMO: Yes | Quality of Service (QoS) support: Yes | Internal memory type: DDR4 | USB port: Yes | Ethernet LAN: Yes | SIM card slot: No | Processor frequency: 1300 MHz | Height: 42 mm | Product type: Tabletop router | LED indicators: LAN, Power, WLAN | Quick start guide: Yes | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | AC input frequency: 50/60 Hz | Ping check: Yes | Operating temperature (T-T): 0 - 40 °C | Ethernet WAN: Yes | Output current: 1.5 A | WLAN data transfer rate (max): 3000 Mbit/s | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | WAN connection type: RJ-45, WISP | Built-in FTP server: Yes | Cloud-managed: Yes | DHCP client: Yes | Wall mountable: Yes | 3G/4G USB modem compatibility: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Number of users: 256 user(s) | Parental control: Yes | Antennas quantity: 5 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | PPPoE/PPTP/L2TP pass-through: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Security algorithms: WPA2-Enterprise | Ethernet LAN data rates: 100 | Modulation: OFDMA | Command-line interface (CLI): Yes | Captive portal: Yes | Networking standards: IEEE 802.11v | VPN server: OpenVPN | Antenna design: Internal | Networking standards: IEEE 802.11ac | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Web-based setup wizard: Yes | Support Samba (storage): Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | AC input voltage: 100 - 240 V | WLAN data transfer rate (first band): 300 Mbit/s | Bandwidth control: Yes | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN data rates: 1000 Mbit/s | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | Networking standards: IEEE 802.11k | Processor manufacturer: MediaTek | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Number of guest networks (5 GHz): 7 | Routing table: Manual | DoS attack prevention: Yes | Weight: 400 g | Port forwarding: Yes | Guest access: Yes | Number of data streams: 3x3 | Flash memory: 256 MB | Mobile operating systems supported: Android | DHCP server: Yes | Ethernet LAN (RJ-45) ports: 4 | Security algorithms: WPA3-Enterprise | IPoE/PPPoE data rate: 1800 Mbit/s | Operating relative humidity (H-H): 20 - 95% | MU-MIMO technology: Yes | Built-in processor: Yes | Intelligent Mesh technology: Yes | Security algorithms: OWE | Housing material: Plastic | Networking standards: IEEE 802.11a | Number of guest networks (2.4 GHz): 7 | System event log: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Traffic statistics: Yes | Schedule access: Yes | WLAN data transfer rate (second band): 2402 Mbit/s | L2TP/PPTP data rate: 900 Mbit/s | Firewall security: SPI | Internet connection backup: Yes | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | WPS push button: Yes | Firewall: Yes | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Security algorithms: WPA-PSK | IPv4 & IPv6 features: IPv6 Telnet | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Number of products included: 1 pc(s) | Mobile operating systems supported: iOS | Output voltage: 12 V | Wi-Fi Multimedia (WMM)/(WME): Yes | Backup function: Yes | Power source type: AC | Width: 170 mm | WireGuard throughput: 460 Mbit/s | IGMP snooping: Yes | Network address translation (NAT): Yes | Media server: Yes | Policy-based routing: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950