



Keenetic Challenger SE (KN-3911) AX3000 Mesh Wi-Fi 6 Multi- Gigabit Router/Extender with Two 2.5 Gigabit Ethernet Ports

Model: KN-3911-01-EU

Manufacturer: KEENETIC

EAN: 4897082922254

Product Code: 300170

R2,361

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | Policy-based routing: Yes | Traffic statistics: Yes | IGMP snooping: Yes | Width: 170 mm | Backup function: Yes | Wall mountable: Yes | Processor cores: 2 | Processor model: MediaTek

MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | USSD request support: Yes | SSID-based VLAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

assignment: Yes | Operating relative humidity (H-H): 20 - 95% | Output voltage: 12 V | Guest access: Yes | WLAN data transfer rate (second band): 2402 Mbit/s | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Number of users: 256 user(s) | Parental control: Yes | PPPoE/PPTP/L2TP pass-through: Yes | Cabling technology: 10/100/1000/2500Base-T | Antennas quantity: 5 | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Ping check: Yes | Flash memory: 128 MB | Port forwarding: Yes | L2TP/PPTP data rate: 2400 Mbit/s | Processor manufacturer: MediaTek | IPv4 & IPv6 features: IPv6 Telnet | Depth: 170 mm | Internal memory: 512 MB | WAN connection type: RJ-45, WISP | Quality of Service (QoS) support: Yes | Mobile operating systems supported: iOS | DoS attack prevention: Yes | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | HTTPS security for access via KeenDNS: Yes | WireGuard throughput: 460 Mbit/s | Number of products included: 1 pc(s) | Schedule access: Yes | WLAN data transfer rate (max): 3000 Mbit/s | Universal Plug and Play (UPnP): Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Ethernet WAN: Yes | Routing table: DHCP | WPS push button: Yes | IPoE/PPPoE data rate: 4800 Mbit/s | Cloud-managed: Yes | Ethernet LAN interface type: 2.5 Gigabit Ethernet | Firewall security: SPI | Internet connection backup: Yes | Housing material: Plastic | WLAN data transfer rate (first band): 300 Mbit/s | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | System event log: Yes | Dynamic DNS (DDNS): Yes | Number of data streams: 3x3 | IntelliQoS: Yes | Mobile operating systems supported: Android | DHCP server: Yes | WireGuard: Yes | Height: 42 mm | Firewall: Yes | Cables included: LAN (RJ-45) | 3G/4G USB modem compatibility: No | Product type: Tabletop router | Built-in processor: Yes | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Command-line interface (CLI): Yes | Ethernet LAN: Yes | SIM card slot: No | Antenna design: Internal | Cloudflare DNS: Yes | MU-MIMO technology: Yes | Web-based setup wizard: Yes | Internal memory type: DDR4 | Output current: 1.5 A | USB port: No | Captive portal: Yes | Number of guest networks (2.4 GHz): 7 | Wi-Fi Multimedia (WMM)/(WME): Yes | Intelligent Mesh technology: Yes | Bandwidth control: Yes | UDP-to-HTTP proxy: Yes | AdGuard ad blocker: Yes | VPN server: OpenVPN | Number of guest networks (5 GHz): 7 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Processor frequency: 1300 MHz | AC input frequency: 50/60 Hz | Security algorithms: WPA2-Enterprise | Security algorithms: OWE | MIMO: Yes | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Quick start guide: Yes | Network address translation (NAT): Yes | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.11a | Weight: 385 g | Product colour: White | AC adapter included: Yes | Networking standards: IEEE 802.11v | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11ac | DHCP client: Yes | Operating temperature (T-T): 0

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- 40 °C | Ethernet LAN (RJ-45) ports: 2 | LED indicators: LAN, Power, WLAN | DC-in jack: Yes | Security algorithms: WPA-PSK | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 2500 Mbit/s | Ethernet LAN data rates: 1000 Mbit/s | Power source type: AC | Firmware upgradeable: Yes | Ethernet LAN data rates: 10

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950