

Keenetic Racer (KN-4010) AX3000 Mesh Wi-Fi 6 Gigabit Router/Extender with Two Gigabit Ethernet Ports



Model: KN-4010-01-EU

Manufacturer: KEENETIC

EAN: 4897082921905

Product Code: 300171

R1,842

Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | DSL WAN: No | Built-in processor: Yes | Cloud-managed: Yes | Universal Plug and Play (UPnP): Yes | System event log: Yes | IGMP snooping: Yes | Backup function: Yes | WLAN data transfer rate (first band): 300 Mbit/s | WLAN data transfer rate (second band): 2402 Mbit/s | Flash memory: 128 MB | Port forwarding: Yes | Firewall security: SPI | 3G/4G USB modem compatibility: No | DoS attack prevention: Yes | Captive portal: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 |

Number of users: 256 user(s) | Parental control: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

Firewall: Yes | SSID-based VLAN assignment: Yes | WPS push button: Yes | Traffic statistics: Yes | Product type: Tabletop router | Dynamic DNS (DDNS): Yes | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Height: 45 mm | IPv4 & IPv6 features: IPv6 Telnet | Mobile operating systems supported: Android | DHCP server: Yes | Guest access: Yes | Automatic channel selection: Yes | Mobile operating systems supported: iOS | Web-based setup wizard: Yes | Policy-based routing: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Number of products included: 1 pc(s) | IPv4 & IPv6 features: IPv6 SSH | Access Control List (ACL): Yes | WAN connection type: RJ-45, WISP | SIM card slot: No | USB port: No | Output current: 1 A | DDoS protection: Yes | Number of guest networks (5 GHz): 7 | Internal memory: 512 MB | Command-line interface (CLI): Yes | MU-MIMO technology: Yes | Antenna design: External | Bandwidth control: Yes | Number of guest networks (2.4 GHz): 7 | Intelligent Mesh technology: Yes | Schedule access: Yes | UDP-to-HTTP proxy: Yes | WireGuard throughput: 460 Mbit/s | IntelliQoS: Yes | AdGuard ad blocker: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Internet connection backup: Yes | IPoE/PPPoE data rate: 1800 Mbit/s | Routing table: DHCP | Ping check: Yes | USSD request support: Yes | PPPoE/PPTP/L2TP pass-through: Yes | WireGuard: Yes | HTTPS security for access via KeenDNS: Yes | L2TP/PPTP data rate: 900 Mbit/s | Cloudflare DNS: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11k | Ethernet LAN data rates: 1000 Mbit/s | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11r | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11ac | Power source type: AC | Product colour: White | Output voltage: 12 V | Security algorithms: WPA-PSK | Internal memory type: DDR4 | Ethernet LAN interface type: Gigabit Ethernet | DHCP client: Yes | Networking standards: IEEE 802.11v | MIMO: Yes | AC input frequency: 50/60 Hz | LED indicators: LAN, Power, WLAN | AC adapter included: Yes | Ethernet LAN data rates: 100 | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet WAN: Yes | Quick start guide: Yes | Cabling technology: 10/100/1000Base-T(X) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Security algorithms: WPA2-PSK | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Ethernet LAN: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Cables included: LAN (RJ-45) | Operating temperature (T-T): 0 - 40 °C | Depth: 118 mm | Ethernet LAN (RJ-45) ports: 2 | Security algorithms: WPA2-Enterprise | Networking standards: IEEE 802.11b | Security algorithms: WEP | Quality of Service (QoS) support: Yes | Security algorithms: OWE | WLAN data transfer rate (max): 3000 Mbit/s | AC input voltage: 100 - 240 V | Antennas quantity: 2 | Processor manufacturer: MediaTek | Processor frequency: 1300 MHz | Security algorithms: WPA3-PSK | Weight: 324 g | Network address translation (NAT): Yes | Operating relative humidity (H-H): 20 - 95% | Width:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

160 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950