

TP-LINK TL- MR6400 wireless router Single-band (2.4 GHz) Fast Ethernet 3G 4G Black



Model: TL-MR6400

Manufacturer: TP-LINK

EAN: 1210002609272

Product Code: 300280

R1,534

Certification: CE, RoHS | Reset button: Yes | Filtering: Yes | DHCP client: Yes | Product colour: Black | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11b | Ethernet LAN data rates: 100 | Stateful Packet Inspection (SPI): Yes | Ethernet LAN data rates: 10 | DC-in jack: Yes | 4G bands supported: 1800 | Detachable antenna(s): Yes | Output current: 0.85 A | 4G bands supported: 900 | Supported network protocols: IPv4, IPv6 | WPS push button: Yes | Universal Plug and Play (UPnP): Yes | Port forwarding: Yes | Height: 33.6 mm | SIM card slot: Yes | Firewall: Yes | Product type: Tabletop router | IP address filtering: Yes | Mobile network generation: 4G | Antenna design: External | DHCP server: Yes | 4G bands supported: 2600 | DMZ

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support: Yes | LED indicators: LAN, Power, WLAN | Wi-Fi standards: Wi-Fi 4 (802.11n) | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Quick start guide: Yes | Wi-Fi standards: 802.11g | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: 802.11b | Output voltage: 9 V | Manual: Yes | 4G bands supported: 1900 | Operating relative humidity (H-H): 10 - 90% | 4G standard: LTE | DSL WAN: No | 4G: Yes | DoS attack prevention: Yes | On/off switch: Yes | WLAN data transfer rate (max): 300 Mbit/s | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 4 | Security algorithms: WPA | Mac compatibility: Yes | Security algorithms: 128-bit WEP | Ethernet LAN interface type: Fast Ethernet | Security algorithms: WPA2-PSK | 3G bands supported: 2100 MHz | Package height: 70 mm | Mac operating systems supported: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Wi-Fi band: Single-band (2.4 GHz) | 3G bands supported: 1900 | Cables included: LAN (RJ-45) | Quick installation guide: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | 3G standards: UMTS | Package weight: 600 g | AC adapter included: Yes | WAN connection type: RJ-45 | 3G: Yes | Antennas quantity: 2 | 4G bands supported: 2100 | 4G bands supported: 800 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Yes | 3G standards: HSPA+ | Package depth: 223 mm | Package width: 307 mm | Ethernet LAN: Yes | USB port: No | Harmonized System (HS) code: 85176990 | Depth: 141 mm | Width: 202 mm | Linux operating systems supported: Yes | Power source type: DC | 3G/4G USB modem compatibility: No | Memory card slot(s): No | Ethernet WAN: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950