

TP-Link Omada 8-Port 2.5G L2+ Managed Switch



Model: SG3210X-M2

Manufacturer: TP-LINK

EAN: 4897098689523

Product Code: 300392

R5,181

Certification: CE, FCC, RoHS | Operating temperature (T-T): 0 - 50 °C | Quick start guide: Yes | Networking standards: IEEE 802.1s | Form factor: 1U | LED indicators: Yes | Ethernet LAN data rates: 100,1000,2500 Mbit/s | Security algorithms: SSL/TLS | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.1w | Security algorithms: SSH-2 | AC input voltage: 100 - 240 V | Product colour: Black | Package weight: 2.84 kg | AC input frequency: 50/60 Hz | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: HTTPS | Security algorithms: SSH | Networking standards: IEEE 802.1D | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package type: Box | Number of IP interfaces: 16 | Number of static routes: 48 | Fanless: Yes | Authentication type: AAA, TACACS+ | Cloud-managed: Yes | GARP VLAN Registration Protocol (GVRP): Yes | 10G support: Yes | Number of VLANs: 4000 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Package depth: 250 mm | Packet buffer memory: 12 MB | Storage relative humidity (H-H): 5 - 90% | Port mirroring: Yes | Link aggregation: Yes | Number of fans: 2 fan(s) | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Console port: RJ-45/micro-USB | Jumbo frames support: Yes | Virtual LAN features: Private VLAN | Virtual LAN features: MAC address-based VLAN | Multicast support: Yes | MAC address table: 16000

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

entries | Depth: 180 mm | Virtual LAN features: Tagged VLAN | Virtual LAN features: Voice VLAN | Spanning tree protocol: Yes | Jumbo frames: 9000 | DHCP features: DHCPv6 snooping | Virtual LAN features: Port-based VLAN | Virtual LAN features: Protocol-based VLAN | DHCP features: DHCPv6 client | Management protocols: SNMPv1/v2c/v3, SNTP | System event log: Yes | Static route: Yes | Password protection: Yes | Power supply included: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Configuring Location Settings (CLI): Yes | Switch layer: L2+ | Package height: 80 mm | Head-of-line (HOL) blocking: Yes | Package width: 528 mm | DHCP features: DHCP snooping | VLAN support: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Traffic classification: Yes | Static port security: Yes | BPDU filtering/protection: Yes | Height: 44 mm | IP-MAC-Port binding: Yes | DHCP features: DHCP server | Cables included: AC | Queue scheduling algorithms: SP | Loop protection: Yes | MIB support: RFC2925, RFC2618, RFC2620, RFC2021, RFC2819, RFC2674, RFC1493, RFC1643, RFC2233, RFC1213 | Switch type: Managed | IGMP snooping: Yes | ARP inspection: Yes | Authentication: MAC-based authentication, Port-based authentication | Queue scheduling algorithms: WRR+SP | SSH/SSL support: Yes | IP routing: Yes | Heat dissipation: 51.18 BTU/h | Access Control List (ACL): Yes | SFP+ module slots quantity: 2 | Switching capacity: 80 Gbit/s | Power consumption (typical): 15 W | Rate limiting: Yes | Rack mounting: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Forwarding rate: 59.52 Mpps | Harmonized System (HS) code: 85176990 | Width: 294 mm | Power source: AC | Power connector: AC-in jack | 2.5G Ethernet (copper) ports quantity: 8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950