

## **iiyama G- MASTER GB2771HSU-B1 computer monitor 68.6 cm (27) 1920 x 1080 pixels Full HD Black**



Model: GB2771HSU-B1

Manufacturer: IIYAMA

EAN: 4948570126439

Product Code: 300435

## **R3,467**

Certification: CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA | Adjustable height (max): 15 cm | Number of downstream ports: 2 | Width (with stand): 612 mm | Cables included: DisplayPort | Operating temperature (T-T): 5 - 35 °C | Height (with stand): 553.5 mm | Storage relative humidity (H-H): 10 - 90% | Swivelling: Yes | DisplayPort version: 1.2 | Cables included: AC | Product colour: Black | Power consumption (off): 0.3 W | On Screen Display (OSD): Yes | HDCP: Yes | Display brightness (typical): 350 cd/m<sup>2</sup> | Viewing angle, horizontal: 178° | Cables included: USB | DisplayPorts quantity: 1 | Touchscreen: No | Package depth: 690 mm | Screen shape: Flat | Package weight: 8.2 kg | Height adjustment: Yes | Operating relative humidity (H-H): 10 - 80% |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Display resolution: 1920 x 1080 pixels | Power supply type: Internal | Vertical scan range: 48 - 240 Hz | AC input frequency: 50 Hz | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 285 kHz | Input current: 1.5 A | Built-in USB hub: Yes | Native aspect ratio: 16:9 | Contrast ratio (dynamic): 80000000:1 | Power consumption (standby): 0.5 W | NVIDIA G-SYNC: Yes | Cable lock slot type: Kensington | Package width: 690 mm | Cables included: HDMI | Power consumption (typical): 19 W | VESA mounting: Yes | Quick start guide: Yes | Headphone outputs: 1 | Display diagonal: 68.6 cm (27") | Depth (with stand): 213 mm | Storage temperature (T-T): -20 - 60 °C | Market positioning: Gaming | Tilt angle range: -5 - 23° | HDMI version: 2.0 | Tilt adjustment: Yes | HD type: Full HD | Pixel pitch: 0.311 x 0.311 mm | Panel mounting interface: 100 x 100 mm | Cable lock slot: Yes | AC input voltage: 100 - 240 V | Package height: 140 mm | Display number of colours: 16.7 million colours | HDMI ports quantity: 2 | Energy consumption (SDR) per 1000 hours: 19 kWh | Energy efficiency class (HDR): G | Number of USB Type-B upstream ports quantity: 1 | Energy consumption (HDR) per 1000 hours: 29 kWh | NVIDIA G-SYNC type: G-SYNC Compatible | Headphone out: Yes | Pivot: Yes | Energy efficiency class (SDR): E | Cable management: Yes | Swivel angle range: -45 - 45° | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10) | Built-in camera: No | Weight (without stand): 3.8 kg | Power cable length: 1.8 m | Low Blue Light technology: Yes | Built-in speaker(s): Yes | Display diagonal (metric): 68.6 cm | Pivot angle: 0 - 90° | Panel type: Fast IPS | High Dynamic Range (HDR) supported: Yes | USB upstream port type: USB Type-B | Number of speakers: 2 | HDMI: Yes | DisplayPort cable length: 1.8 m | Weight (with stand): 5.6 kg | Height (without stand): 408.5 mm | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | On Screen Display (OSD) languages: Multi | Number of OSD languages: 10 | VESA Adaptive Sync support: Yes | Warnings: The monitor contains materials that may be harmful to the environment follow local regulations for the disposal of electronic devices. | Viewable size, vertical: 33.6 cm | Response time (MPRT): 0.4 ms | RMS rated power: 4 W | Contrast ratio (typical): 1000:1 | Energy efficiency scale: A to G | HDMI cable length: 1.8 m | Warnings: Avoid direct contact with liquids. | Warnings: Do not expose to water or excessive moisture. | Maximum refresh rate: 240 Hz | USB Type-A downstream ports quantity: 2 | Headphone connectivity: 3.5 mm | AMD FreeSync: Yes | Colour depth: 8 bit | Haze rate: 25% | DDC/CI: Yes | European Product Registry for Energy Labelling (EPREL) code: 2435254

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950