

TP-Link TL- SG1048 Unmanaged Gigabit Ethernet (10/100/1000) 1U Black



Model: TL-SG1048

Manufacturer: TP-LINK

EAN: 1210002611381

Product Code: 300596

R6,140

Certification: FCC, CE, RoHS | LED indicators: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 16 MB | Switch type: Unmanaged | Auto MDI/MDI-X: Yes | Product colour: Black | Operating temperature (T-T): 0 - 40 °C | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Store-and-forward: Yes | Jumbo frames: 10000 | Depth: 220 mm | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 10 - 90% | Number of fans: 2 fan(s) | Basic switching RJ-45 Ethernet ports quantity: 48 | Form factor: 1U | Rack mount kit: Yes | Storage temperature (T-T): -40 - 70 °C | Quick start guide: Yes | Switching capacity: 96 Gbit/s | Power consumption (max): 29.8 W | Power supply included: Yes | Jumbo frames support: Yes | Storage relative humidity (H-H): 5 - 90% | Height: 44 mm | Harmonized System (HS) code: 85176990 | Rack mounting: Yes | Cables included: AC | Throughput: 71.4 Mpps | Width: 440 mm | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3u |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3i

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950