

## TP-Link Archer MR202 wireless router Fast Ethernet Dual- band (2.4 GHz 5 GHz) 4G Black



Model: MR202

Manufacturer: TP-LINK

EAN: 8885020625745

Product Code: 300614

# R1,342

Certification: CE, RoHS | Receiver sensitivity: 5 GHz: 11a 54M: -78 dBm 11ac VHT20: -92 dBm 11ac VHT20: -72 dBm 11ac VHT40: -90 dBm 11ac VHT40: -67 dBm 11ac VHT80: -87 dBm 11ac VHT80: -64 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -91 dBm 11n HT20: -72 dBm 11n HT40: -88 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, OpenVPN | Ethernet LAN data rates: 10 | Product colour: Black | Stateful Packet Inspection (SPI): Yes | Ethernet LAN data rates: 100 | LED indicators: LAN, Power, WAN, WLAN | Networking standards: IEEE 802.11b | Reset button: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Web-based management: Yes | DHCP client: Yes | DC-in jack: Yes | Windows operating systems supported: Windows NT | Wi-Fi standards: 802.11g | Windows operating systems supported: Windows 2000 | Operating temperature (T-T): 0 - 40 °C |

Product type: Tabletop router | Windows operating systems supported: Windows 8 | Wi-Fi standards:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

802.11b | Height: 33.5 mm | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | 4G bands supported: 700 | 4G bands supported: 2300 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | Ethernet LAN (RJ-45) ports: 3 | UMTS bands supported: 900 | Windows operating systems supported: Windows 7 | Cables included: LAN (RJ-45) | Firewall: Yes | Mac operating systems supported: Yes | DSL WAN: No | DoS attack prevention: Yes | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | Quick installation guide: Yes | Wi-Fi standards: 802.11a | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | Windows operating systems supported: Windows 98SE | Firewall security: IP and MAC Address Binding | 4G: Yes | Output voltage: 12 V | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | WAN connection type: RJ-45 | Security algorithms: WPA2-PSK | Output current: 1 A | 4G standard: LTE-TDD & LTE-FDD | 3G: Yes | Antennas quantity: 2 | 4G bands supported: 2100 | 4G bands supported: 800 | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | Ethernet LAN interface type: Fast Ethernet | Security algorithms: 128-bit WEP | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Memory card slot(s): No | Security algorithms: WPA | Power source type: DC | Linux operating systems supported: Yes | Dynamic DNS (DDNS): Yes | Supported network protocols: IPv4, IPv6 | WLAN data transfer rate (max): 733 Mbit/s | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Ethernet LAN: Yes | Port forwarding: Yes | Width: 174 mm | Depth: 124.5 mm | USB port: No | SIM card slot: Yes | 3G standards: UMTS | DMZ support: Yes | Operating relative humidity (H-H): 10 - 90% | Port triggering: Yes | 3G standards: HSPA | WLAN data transfer rate (second band): 433 Mbit/s | DHCP server: Yes | Transmit power: 20dBm(2.4G) 23dBm(5G) | Plug and Play: Yes | Guest access: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Dynamic IP: Yes | Universal Plug and Play (UPnP): Yes | Static IP: Yes | Ethernet WAN: Yes | Antenna design: External | Point-to-point protocol over Ethernet (PPPoE): Yes | Number of Ethernet LAN/WAN ports: 1 | Warnings: Do not expose the device to water or moisture. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures.

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950