

DELL Pro Plus P2425DE computer monitor 61 cm (24) 2560 x 1440 pixels Quad HD LCD Black



Model: 210-BRDM

Manufacturer: DELL

EAN: 5397184962466

Product Code: 300636

R5,817

Height adjustment: Yes | Digital horizontal frequency: 30 - 150 kHz | On Screen Display (OSD): Yes |
Market positioning: Office | Height (without stand): 315.2 mm | Pixel density: 123 ppi | Doesn't
contain: Arsenic | USB Power Delivery (USB PD): Yes | Response time (fast): 5 ms | Doesn't contain:
PVC/BFR | Display technology: LCD | Energy consumption (SDR) per 1000 hours: 17 kWh | Carbon
emissions, manufacturing (kg of CO₂e): 86.394 | Doesn't contain: Mercury | Built-in USB hub: Yes |
VESA mounting: Yes | Depth (without stand): 49.7 mm | Carbon emissions, energy usage (kg of
CO₂e): 80.971 | AMD FreeSync: No | Power supply type: Internal | Power consumption (typical): 16.5

W | RJ-45 ports quantity: 1 | Digital vertical frequency: 48 - 100 Hz | Number of USB Type-C upstream

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ports quantity: 1 | Pivot angle: -90 - 90° | Touchscreen: No | sRGB coverage (typical): 99% | USB upstream port type: USB Type-C | Power consumption (standby): 0.3 W | Viewable size, horizontal: 52.7 cm | HDMI version: 2.1 | Backlight type: Edge LED | Built-in speaker(s): No | Headphone out: No | Carbon emissions, logistics (kg of CO2e): 14.212 | Wall mountable: Yes | Viewable size, vertical: 29.6 cm | Surface hardness: 3H | Panel type: IPS | Energy efficiency class (SDR): E | Contrast ratio (typical): 1500:1 | Anti-glare screen: Yes | HDMI ports quantity: 1 | Width (without stand): 538.7 mm | HDMI: Yes | Low Blue Light technology: Yes | Weight (without stand): 3.78 kg | Tilt adjustment: Yes | Carbon emissions, end-of-life (kg of CO2e): 5.236 | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Supported video modes: 1080i | Plug and Play: Yes | Swivel angle range: -45 - 45° | USB Power Delivery up to: 90 W | USB Type-A downstream ports quantity: 3 | Supported video modes: 576p | Panel mounting interface: 100 x 100 mm | Energy efficiency scale: A to G | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Pivot: Yes | Built-in camera: No | USB Type-C DisplayPort Alternate Mode: Yes | Ethernet LAN: Yes | HDCP version: 1.4 | Swivelling: Yes | Supported video modes: 720p | Supported video modes: 1440p | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Non-operating altitude: 5000 - 12191 m | Maximum refresh rate: 100 Hz | Weight (with stand): 5.25 kg | DisplayPort cable length: 1.8 m | Supported video modes: 480p | Supported video modes: 1080p | Stand included: Yes | Energy efficiency class (HDR): Not available | Total carbon footprint (kg of CO2e): 187 | DisplayPort out quantity: 1 | Compliance certificates: RoHS | Adjustable height (max): 15 cm | PAIA version: GaBi version 1, 2024 | European Product Registry for Energy Labelling (EPREL) code: 2151603 | Warnings: Unplug the monitor from the power source before cleaning. | Response time measurement type: GTG (Gray to Gray) | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Width (with stand): 538.7 mm | Total carbon emissions, w/o use phase (kg of CO2e): 106.029 | Native aspect ratio: 16:9 | LED indicators: Yes | AC input voltage: 100 - 240 V | Tilt angle range: -5 - 21° | Display brightness (typical): 250 cd/m² | NVIDIA G-SYNC: No | Operating altitude: 0 - 5000 m | HDCP: Yes | Screen shape: Flat | Display diagonal: 61 cm (24") | Depth (with stand): 181.5 mm | Cable lock slot type: Kensington | Pixel pitch: 0.2058 x 0.2058 mm | Height (with stand): 496.6 mm | Cables included: DisplayPort | Cables included: USB Type-A to USB Type-C | Package weight: 7.57 kg | LED backlight: Yes | HD type: Quad HD | Viewing angle, horizontal: 178° | Storage temperature (T-T): -20 - 60 °C | DisplayPorts quantity: 1 | Power consumption (max): 185 W | Storage relative humidity (H-H): 5 - 90% | DisplayPort version: 1.4 | Cable lock slot: Yes | Power consumption (off): 0.3 W | Product colour: Black | Operating temperature (T-T): 0 - 40 °C | Display number of colours: 16.7 million colours | Cables included: AC | Response time: 8 ms | Viewing angle, vertical: 178° | Display resolution: 2560 x 1440 pixels | AC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

input frequency: 50/60 Hz | Cables included: USB Type-C to USB Type-C | Operating relative humidity (H-H): 10 - 80%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950