

## **DELL P Series P2425E computer monitor 61.1 cm (24.1) 1920 x 1200 px WUXGA LCD, black**



Model: 210-BMJF

Manufacturer: DELL

EAN: 5397184821688

Product Code: 300643

## **R4,600**

Dell Display Manager (DDM) compatibility: Yes | USB Power Delivery up to: 90 W | Display diagonal: 61.1 cm (24.1") | Native aspect ratio: 16:10 | Depth (with stand): 181.8 mm | USB Type-C DisplayPort Alternate Mode: Yes | Pixel density: 94.07 ppi | Weight (without stand): 3.51 kg | Anti-glare screen: Yes | Width (without stand): 531.8 mm | Cable management: Yes | Low Blue Light technology: Yes | LED indicators: Yes | Energy consumption (SDR) per 1000 hours: 15 kWh | NVIDIA G-SYNC: No | Display resolution: 1920 x 1200 pixels | AC input frequency: 50/60 Hz | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | DisplayPort version: 1.4 | Doesn't contain: Mercury | HD type: WUXGA | Energy efficiency scale: A to G | Power consumption (off): 0.3 W | Doesn't contain: Arsenic | Input current: 2 A | LED backlight: Yes | USB Type-C downstream ports quantity: 1 | Height

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(with stand): 364 mm | DisplayPort cable length: 1.8 m | DisplayPorts quantity: 2 | Tilt angle range: -5 - 21° | Sustainability certificates: RoHS | Sustainability certificates: TÜV mark | HDCP version: 1.4 | sRGB coverage (typical): 99% | Dell ComfortView technology: Yes | Response time: 8 ms | Quick start guide: Yes | HDCP: Yes | Surface hardness: 3H | Height (without stand): 343.7 mm | Sustainability compliance: Yes | Response time (fast): 5 ms | AC input voltage: 100 - 240 V | RJ-45 ports quantity: 1 | Front bezel colour: Black | Energy efficiency class (HDR): Not available | Display brightness (typical): 300 cd/m<sup>2</sup> | Product colour: Black | Cable lock slot: Yes | Doesn't contain: PVC/BFR | Depth (without stand): 50 mm | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | HDMI: Yes | Bezel width (top): 6.7 mm | Width (with stand): 531.8 mm | Screen shape: Flat | Network card: Yes | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Number of USB Type-C upstream ports quantity: 1 | USB Power Delivery (USB PD): Yes | Supported graphics resolutions: 720 x 400 | USB cable length: 1 m | Supported graphics resolutions: 1600 x 1200 | Supported graphics resolutions: 1152 x 864 (XGA+) | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1280 x 1024 (SXGA) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Energy efficiency class (SDR): D | Supported graphics resolutions: 1280 x 720 (HD 720) | Ethernet LAN (RJ-45) ports: 1 | Cable lock slot type: Kensington | Pivot angle: -90 - 90° | Weight (with stand): 5.02 kg | Mac operating systems supported: MacOS | Touchscreen: No | Backlight type: LED | Height adjustment: 15 cm | Pixel pitch: 0.27 x 0.27 mm | Panel mounting interface: 100 x 100 mm | Non-operating altitude: 0 - 12192 m | Contrast ratio (typical): 1500:1 | AC (power) in: Yes | Plug and Play: Yes | Display number of colours: 16.7 million colours | Cables included: DisplayPort | Swivel angle range: -45 - 45° | Bezel width (side): 6.7 mm | Operating temperature (T-T): 0 - 40 °C | Viewable size, horizontal: 51.8 cm | Bezel width (bottom): 1.3 cm | Built-in speaker(s): No | Headphone out: No | USB Type-A downstream ports quantity: 3 | Cables included: USB | Swivelling: Yes | Viewable size, vertical: 32.4 cm | Operating altitude: 0 - 5000 m | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Storage temperature (T-T): -20 - 60 °C | Pivot: Yes | Stand included: Yes | On Screen Display (OSD): Yes | Operating relative humidity (H-H): 10 - 80% | Height adjustment: Yes | Power consumption (typical): 15 W | Supported video modes: 480p | Supported video modes: 1080p | Viewing angle, horizontal: 178° | Built-in USB hub: Yes | Power consumption (standby): 0.3 W | Feet colour: Grey | Maximum refresh rate: 100 Hz | Power consumption (max): 190 W | HDMI ports quantity: 1 | HDMI version: 1.4 | Built-in camera: No | Supported video modes: 720p | Flicker-free technology: Yes | Storage relative humidity (H-H): 5 - 90% | Display technology: LCD | Tilt adjustment: Yes | VESA mounting: Yes |

**Windows operating systems supported: Windows 10 | Cables included: AC | Viewing angle, vertical:**

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

178° | Supported video modes: 576p | Windows operating systems supported: Yes | AMD FreeSync: No | Panel type: IPS | Viewable size diagonal: 61.1 cm | Vertical scan range: 48 - 100 Hz | Power supply type: Internal

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950