

TP-Link EX141 wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) Black



Model: EX141

Manufacturer: TP-LINK

EAN: 4895252502312

Product Code: 300752

R1,173

VPN support: IPSec, PPTP, L2TP | NAT functionality: ALG, Virtual Server, Port Trigger, DMZ, uPnP | Security algorithms: WPA2 | Security algorithms: IPSec | Security algorithms: WPA | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN: Yes | SIM card slot: No | Depth: 94 mm | Product colour: Black | Quick installation guide: Yes | Product type: Tabletop router | Firewall: Yes | DHCP client: Yes | Security algorithms: SSID | Ethernet LAN (RJ-45) ports: 4 | Cables included: LAN (RJ-45) | WPS push button: Yes | VPN Passthrough: Yes | Modulation: 1024-QAM | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | Operating temperature (T-T): 0 - 40 °C | DHCP server: Yes | Port forwarding: Yes | USB port: No | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Height: 33.3 mm | Quality of Service (QoS) support: Yes | 3G/4G USB modem compatibility: No | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 1201 Mbit/s | DMZ support: Yes | Ethernet LAN data rates: 1000 Mbit/s | Mac

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

operating systems supported: Yes | Output voltage: 12 V | Width: 182.7 mm | Network address translation (NAT): Yes | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Port triggering: Yes | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browsers or higher | Windows operating systems supported: Yes | Ethernet LAN data rates: 10 | Output current: 1 A | Ethernet WAN: Yes | WAN connection type: RJ-45 | Management protocols: TR-069, TR-098, TR-181, TR-111, and TR-143 | Power source type: DC | Linux operating systems supported: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Ethernet LAN data rates: 100 | Wi-Fi standards: Wi-Fi 4 (802.11n) | WLAN data transfer rate (first band): 300 Mbit/s | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Cabling technology: 10/100/1000Base-T(X) | Wi-Fi standards: 802.11b | Parental control: Yes | Wi-Fi standards: 802.11g | Antennas quantity: 4 | WLAN data transfer rate (second band): 1201 Mbit/s | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | MU-MIMO technology: Yes | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Antenna design: External | VPN server: PPTP, OpenVPN, IPSec | Warnings: Do not open the appliance housing - risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950