

## HP Series 7 Pro 34 inch WQHD Conferencing Monitor - 734pm



Model: 8K157UT

Manufacturer: HEWLETT-PACKARD

EAN: 198415143440

Product Code: 300803

## R21,454

Bundled software: HP Display Center HP Client Management Script Library | Certification: BIS BSMI  
CB CCC CE CECP CEL EAC FCC ISO 9241-307 KC KCC NOM PSB RCM SEPA TUV-S UL/CSA VCCI WEEE  
ISC Low blue light WW application ICE UAE GS Ukraine EE Belarus EE Korea MEPS CEL Grade 2 |  
Manufacturer warranty: HP three-year limited warranty | Energy efficiency scale: A to G | VESA  
Adaptive Sync support: Yes | USB Power Delivery up to: 100 W | DisplayPort out quantity: 1 |  
DisplayPort out version: 1.4 | Response time measurement type: GTG (Gray to Gray) | sRGB  
coverage (typical): 100% | General Product Safety Regulation (GPSR) URL:  
<https://support.hp.com/gb-en/product/setup-user-guides/hp-deskjet-2700-all-in-one-printer-series/model/31598160?sku=5AR83B&serialnumber=5AR83B> | USB Type-C DisplayPort Alternate  
Mode: Yes | Remotely operated: Yes | Compliance certificates: Federal Communications Commission  
(FCC) | Compliance certificates: CB | Compliance certificates: EAC | Compliance certificates: CCC |  
Compliance certificates: BIS | Compliance certificates: CE | UNSPSC-code: 43211902 | Compliance  
certificates: BSMI | Fast charging: Yes | USB Power Delivery (USB PD): Yes | Cables included:

DisplayPort | Compliance certificates: CECP | High Dynamic Range (HDR) supported: Yes | Cables

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or  
typographical errors. We recommend checking the current information before purchasing.

included: Thunderbolt | Number of USB Type-C upstream ports quantity: 1 | Anti-glare screen: Yes | Vertical scan range: 30 - 120 Hz | Feet colour: Silver | High Dynamic Range (HDR) technology: DisplayHDR 400 | USB hub version: 3.2 Gen 2 (3.1 Gen 2) | Low Blue Light technology: Yes | Warranty card: Yes | Built-in KVM switch: Yes | Panel mounting interface: 100 x 100 mm | Width (without stand): 813.8 mm | HDMI: Yes | Depth (without stand): 120.2 mm | AMD FreeSync type: FreeSync Premium | USB Type-C downstream ports quantity: 1 | Flicker-free technology: Yes | Sustainability certificates: EPEAT Climate + | Cables included: USB Type-C to USB Type-A | Weight (with stand): 11.3 kg | Detachable stand: Yes | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Thunderbolt 4 ports quantity: 2 | Display brightness: 400 cd/m<sup>2</sup> | Cables included: HDMI | Sustainability compliance: Yes | HDMI version: 2.0 | Weight (without stand): 8.78 kg | Picture-in-Picture: Yes | Energy consumption (SDR) per 1000 hours: 32.5 kWh | Height (without stand): 364.1 mm | Energy efficiency class (HDR): G | HP segment: Business | Surface hardness: 3H | Pixel density: 109 ppi | Sustainability certificates: EPEAT | Sustainability certificates: TCO10 | Screen curvature rating: 1900R | Horizontal scan range: 30 - 190 kHz | Maximum refresh rate: 120 Hz | Built-in USB hub: Yes | Power consumption (typical): 51 W | Cables included: AC | Haze rate: 25% | Feet colour: Black | Colour gamut standard: DCI-P3 | Colour gamut standard: sRGB | Energy efficiency class (SDR): G | Package height: 485 mm | Microphone in: Yes | Package depth: 226 mm | Energy consumption (HDR) per 1000 hours: 68 kWh | Swivelling: Yes | Height: 364.1 mm | Panel type: IPS Black | Viewable size, vertical: 33.5 cm | Number of speakers: 4 | Megapixel (approx.): 5 MP | Display technology: LCD | Display diagonal (metric): 86.4 cm | On Screen Display (OSD): Yes | Height adjustment: Yes | Power supply type: Internal | AMD FreeSync: Yes | European Product Registry for Energy Labelling (EPREL) code: 1894961 | Market positioning: Business | Backlight type: Edge LED | Ethernet LAN: Yes | VESA mounting: Yes | Power consumption (standby): 0.5 W | Built-in camera: Yes | Tilt adjustment: Yes | Depth: 120.2 mm | Touchscreen: No | Non-operating altitude: 0 - 12192 m | Built-in speaker(s): Yes | Colour gamut: 100% | Colour depth: 8 bit | Contrast ratio (typical): 2000:1 | Audio decoders: DTS Virtual:X | Viewable size, horizontal: 80 cm | Width: 813.8 mm | USB Type-A downstream ports quantity: 5 | RMS rated power: 12 W | HDMI ports quantity: 1 | Warnings: Unplug the monitor from the power source before cleaning. | Adjustable height (max): 15 cm | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Infrared (IR) sensor: Yes | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | DisplayPorts quantity: 1 | Response time: 5 ms | AC input frequency: 50/60 Hz | Display resolution: 3440 x 1440 pixels | DisplayPort version: 1.4 | LED backlight: Yes | Native aspect ratio: 21:9 | Weight: 11.3 kg | Quick start guide: Yes | Product colour: Black | AC input voltage: 100 - 240 V | HDCP: Yes | Cable lock slot: Yes | Height (with stand): 547.4 mm | Display brightness

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(typical): 400 cd/m<sup>2</sup> | Built-in microphone: Yes | Tilt angle range: -5 - 20° | Screen shape: Curved | Power consumption (off): 0.3 W | HD type: Wide Quad HD | Width (with stand): 813.8 mm | Display surface: Matt | Package width: 952 mm | Display diagonal: 86.4 cm (34") | Depth (with stand): 266.9 mm | Aspect ratio: 21:9 | Pixel pitch: 0.23 x 0.23 mm | Package weight: 17.4 kg | Display number of colours: 16.7 million colours | Package type: Box | Operating altitude: 0 - 5000 m | Ethernet LAN (RJ-45) ports: 1 | Storage relative humidity (H-H): 20 - 80% | Viewing angle, horizontal: 178° | NVIDIA G-SYNC: No | Operating relative humidity (H-H): 20 - 80% | Power consumption (max): 310 W | Operating temperature (T-T): 5 - 35 °C | Viewing angle, vertical: 178° | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Supported graphics resolutions: 1600 x 900 | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 1280 x 1024 (SXGA) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Supported graphics resolutions: 720 x 400 | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) | Supported graphics resolutions: 3440 x 1440

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950