

HP Series 7 Pro 37.5 inch WQHD+ Thunderbolt 4 Monitor - 738pu



Model: 8K167AA

Manufacturer: HEWLETT-PACKARD

EAN: 197497776584

Product Code: 300804

R21,829

Bundled software: HP Display Center HP Client Management Script Library | Certification: BIS BSMI CB CCC CE CECP CEL EAC FCC ISO 9241-307 KC KCC NOM PSB RCM SEPA TUV-S UL/CSA VCCI WEEE ISC Low blue light ICE UAE GS Ukraine EE Belarus EE Korea MEPS CEL Grade 2 | Manufacturer warranty: HP three-year limited warranty | Surface hardness: 3H | USB Power Delivery up to: 100 W | Vertical scan range: 30 - 60 Hz | AMD FreeSync: No | VESA mounting: Yes | Quick start guide: Yes | Height adjustment: Yes | Viewing angle, horizontal: 178° | Market positioning: Business | Anti-glare screen: Yes | Storage relative humidity (H-H): 20 - 80% | Screen shape: Curved | Power consumption (standby): 0.5 W | Display technology: LCD | Operating altitude: 0 - 5000 m | Power supply type: Internal | Built-in USB hub: Yes | High Dynamic Range (HDR) technology: DisplayHDR 400 | Ethernet LAN: Yes | Digital vertical frequency: 30 - 60 Hz | Package height: 527 mm | Package type: Box | NVIDIA G-SYNC: No | Backlight type: Edge LED | Built-in camera: No | Digital horizontal frequency: 30 - 140 kHz | Package depth: 226 mm | Weight (with stand): 12.2 kg | Haze rate: 25% | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

consumption (typical): 62 W | USB hub version: 3.2 Gen 2 (3.1 Gen 2) | Panel type: IPS Black | DisplayPorts quantity: 1 | Weight: 12.2 kg | Depth: 108.4 mm | Tilt adjustment: Yes | Package weight: 18.9 kg | Cables included: USB Type-C to USB Type-A | Cables included: DisplayPort | Display diagonal (metric): 95.3 cm | Height: 396.9 mm | Cables included: Thunderbolt | Cables included: AC | HD type: Wide Quad HD+ | Number of speakers: 4 | Cables included: HDMI | Package width: 1060 mm | Power consumption (max): 318 W | Height (with stand): 581 mm | Viewing angle, vertical: 178° | On Screen Display (OSD): Yes | Viewable size, vertical: 36.6 cm | Display brightness: 400 cd/m² | DisplayPort version: 1.4 | Swivelling: Yes | Operating relative humidity (H-H): 20 - 80% | Horizontal scan range: 30 - 140 kHz | Panel mounting interface: 100 x 100 mm | HDMI version: 2.0 | Built-in speaker(s): Yes | Ethernet LAN (RJ-45) ports: 1 | Viewable size, horizontal: 88 cm | Contrast ratio (typical): 2000:1 | Non-operating altitude: 0 - 12192 m | Display number of colours: 1.07 billion colours | Operating temperature (T-T): 5 - 35 °C | Pixel pitch: 0.23 x 0.23 mm | USB Type-A downstream ports quantity: 5 | Supported graphics resolutions: 1600 x 900 | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Supported graphics resolutions: 3840 x 1600 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | RMS rated power: 12 W | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Supported graphics resolutions: 2560 x 1600 (WQXGA) | Supported graphics resolutions: 720 x 400 | Supported graphics resolutions: 1280 x 1024 (SXGA) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Width: 894.4 mm | Supported graphics resolutions: 2560 x 1440 | Energy consumption (SDR) per 1000 hours: 37.9 kWh | Sustainability certificates: EPEAT | Sustainability certificates: TCO10 | HDMI ports quantity: 1 | Screen curvature rating: 2300R | Headphone out: No | Thunderbolt 4 ports quantity: 2 | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Picture-in-Picture: Yes | UNSPSC-code: 43211902 | Sustainability certificates: EPEAT Climate + | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Stand included: Yes | High Dynamic Range (HDR) supported: Yes | Low Blue Light technology: Yes | Sustainability compliance: Yes | HP segment: Business | USB Type-C DisplayPort Alternate Mode: Yes | Energy efficiency class (HDR): G | USB Power Delivery (USB PD): Yes | Pixel density: 111 ppi | Energy consumption (HDR) per 1000 hours: 75 kWh | Number of USB Type-C upstream ports quantity: 1 | Fast charging: Yes | Remotely operated: Yes | sRGB coverage (typical): 100% | Height (without stand): 396.9 mm | Detachable stand: Yes | Feet colour: Black | Colour depth: 10 bit | Warranty card: Yes | Width (without stand): 894.4 mm | Audio decoders: DTS Virtual:X | Built-in KVM switch: Yes | Depth (without stand): 108.4 mm | Feet colour: Silver | HDMI: Yes | Energy efficiency

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

scale: A to G | Energy efficiency class (SDR): G | Colour gamut: 100% | Maximum refresh rate: 60 Hz | Carbon emissions, logistics (kg of CO2e): 2 | Total carbon emissions, w/o use phase (kg of CO2e): 4 | Carbon emissions, end-of-life (kg of CO2e): 2 | Carbon emissions, manufacturing (kg of CO2e): 30 | Total carbon footprint (kg of CO2e): 40 | Colour gamut standard: sRGB | Compliance certificates: CE | Compliance certificates: BIS | Compliance certificates: CECP | Compliance certificates: BSMI | Compliance certificates: Federal Communications Commission (FCC) | European Product Registry for Energy Labelling (EPREL) code: 1900717 | Colour gamut standard: DCI-P3 | Compliance certificates: CCC | Compliance certificates: CB | Compliance certificates: EAC | Adjustable height (max): 15 cm | General Product Safety Regulation (GPSR) URL: <https://support.hp.com/gb-en/product/setup-user-guides/hp-deskjet-2700-all-in-one-printer-series/model/31598160?sku=5AR83B&serialnumber=5AR83B> | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Response time measurement type: GTG (Gray to Gray) | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Display brightness (typical): 400 cd/m² | AC input frequency: 50/60 Hz | HDCP: Yes | LED backlight: Yes | Display diagonal: 95.2 cm (37.5") | Response time: 5 ms | Power consumption (off): 0.3 W | Product colour: Black | Native aspect ratio: 21:9 | Tilt angle range: -5 - 20° | Display resolution: 3840 x 1600 pixels | Width (with stand): 894.4 mm | AC input voltage: 100 - 240 V | Display surface: Matt | Aspect ratio: 21:9 | Depth (with stand): 266.9 mm | Cable lock slot: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950