

TP-Link 9-Port 10/100Mbps Desktop Switch with 8-Port PoE+



Model: TL-SF1009P

Manufacturer: TP-LINK

EAN: 6935364052966

Product Code: 300899

R951

Certification: FCC, CE, RoHS | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3i | Copper ethernet cabling technology: 100BASE-TX | Power consumption (max): 77.08 W | AC input frequency: 50 Hz | Networking standards: IEEE 802.3at | Power supply included: No | Networking standards: IEEE 802.3x | Housing material: Metal | Depth: 98 mm | Copper ethernet cabling technology: 10BASE-T | Storage relative humidity (H-H): 5 - 90% | Height: 27 mm | Package weight: 980 g | Networking standards: IEEE 802.3af | Package height: 68 mm | Power over Ethernet (PoE) power per port: 30 W | Switching capacity: 1.6 Gbit/s | Networking standards: IEEE 802.3u | LED indicators: PoE | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Package width: 223 mm | Package type: Box | Power over Ethernet (PoE): Yes | AC input voltage: 220 V | Input current: 1.31 A | LED indicators: Activity | Auto MDI/MDI-X: Yes | Harmonized System (HS) code: 85176990 | Total Power over Ethernet (PoE) budget: 65 W | Package depth: 280 mm | Product colour: Black | Width: 171 mm | LED indicators: Link | Power source: DC/PoE | LED indicators: Power | Operating

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

temperature (T-T): 0 - 40 °C | AC adapter included: Yes | Rack mounting: No | Power connector: DC-in jack | Forwarding rate: 1.3392 Mpps | DC input voltage: 53.5 V | Stackable: No | Full duplex: Yes | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Cable types supported: Cat5 | Cable types supported: Cat5e | MAC address auto-aging supported: Yes | Power over Ethernet plus (PoE+) ports quantity: 8 | Heat dissipation: 262.84 BTU/h | Cable types supported: Cat4 | MAC address auto-learning supported: Yes | Wall mountable: Yes | 10G support: No | Auto-negotiation: Yes | Flow control support: Yes | Cable types supported: Cat3 | Basic switching RJ-45 Ethernet ports quantity: 9 | Fanless: Yes | Switch type: Unmanaged | Store-and-forward: Yes | Fast Ethernet (copper) ports quantity: 9 | MAC address table: 2000 entries | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Compliance certificates: RoHS | Compliance certificates: CE | Half duplex: Yes | Warnings: Do not open the case or try to repair it yourself. | Sustainability compliance: Yes | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950