

Iiyama XUB2792UHSU- B6 27inch IPS UHD 60Hz 350cd/m2 4ms HDMI DP Speakers (P)



Model: XUB2792UHSU-B6

Manufacturer: Iiyama

EAN: 4948570123803

Product Code: 301261

R7,017

The Iiyama ProLite XUB2792UHSU-B6 is a testament to the fusion of performance and ergonomic design. This 27-inch LED-backlit LCD monitor not only boasts a 4K UHD resolution for clarity and detail but also covers 100% sRGB and 72% NTSC color gamuts, ensuring professional-grade color accuracy for graphic design, photo editing, and more.

Ergonomics are central to the design of the XUB2792UHSU-B6, offering users a full range of display position adjustments including height, pivot, swivel, and tilt, facilitating an optimal viewing experience that can significantly reduce physical strain during long periods of use. Additionally, the monitor features advanced connectivity options, including HDMI, DisplayPort, and USB-C, allowing for easy integration into any workspace.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Moreover, the iiyama ProLite XUB2792UHSU-B6 is equipped with eye care technology, including Flicker-Free technology and a Blue Light Reducer Function, to ensure comfort during extended use. This, combined with its ultraslim design and dynamic power saving features, makes it an excellent choice for professionals seeking a blend of performance, comfort, and sustainability.

Product Description: iiyama ProLite XUB2792UHSU-B6 - LED monitor - 4K - 27" | Device Type: LED-backlit LCD monitor - 27" | Energy Class: Class F | Features: USB 3.2 Gen 1 hub, USB PD 15 Watt | Panel Type: IPS | Aspect Ratio: 16:9 | Native Resolution: 4K 3840 x 2160 at 60 Hz | Pixel Pitch: 0.155 mm | Brightness: 350 cd/m² | Contrast Ratio: 1300:1 / 80000000:1 (dynamic) | Response Time: 4 ms (grey-to-grey) | Colour Support: 1.07 billion colours | Colour Gamut: 100% sRGB, 72% NTSC | Input Connectors: HDMI, DisplayPort, USB-C | Display Position Adjustments: Height, pivot (rotation), swivel, tilt | Screen Coating: Matte | Voltage: AC 100-240 V (50/60 Hz) | Colour: Matte black | Dimensions (WxDxH) - with stand (lowest position): 61.45 cm x 20.95 cm x 39.75 cm | Weight: 6.3 kg | Environmental Standards: TCO Certified Displays 9 | Compliant Standards: TUV GS, VCCI, DDC-2B, RoHS, WEEE, PSE Mark, REACH, ERP, EAC, UKCA | Manufacturer Warranty: 3-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950