

LANBERG switch PoE+ rack 19inch 24x 1GB 2x SFP 250W RSGE-24P-2GE- 2S-250 unmanaged



Model: RSGE-24P-2GE-2S-250

Manufacturer: LANBERG

EAN: 5901969438680

Product Code: 301399

R3,078

The PoE+ switch is an essential active networking device in any Ethernet infrastructure using power transmission through structural cabling. RSGE-24P-2GE-2S-250 is dedicated to all kinds of installations: home, business, low-voltage, surveillance, IP, VoIP, cable TV networks, and in a particular product can be used in alarm, fire, or access control system.

Apart from the switch's primary function, i.e., supporting Ethernet frame transfer between ports, the device also provides a power supply for each appliance in PoE/PoE+ standard - 802.3af/at. This means that the switch can supply the devices with a total of up to 250 W. All of this is combined with data transmission at the same time.

As a result, such a solution saves resources, space, and time to install a separate electrical and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

network infrastructure. This is especially important if the network is dispersed and its end-devices do not have direct access to the power source, in particular, when they are mounted outside.

Product Description: Lanberg RSGE-24P-2GE-2S-250 - switch - 24 ports - unmanaged - rack-mountable | Device Type: Switch - 24 ports - unmanaged | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000Base-TX (PoE+) + 2 x 1000Base-X SFP + 2 x 1000Base-X (uplink) | Power Over Ethernet (PoE): PoE+ | PoE Budget: 250 W | Performance: Bandwidth: 56 Gbps | MAC Address Table Size: 8K entries | Features: 4KV ESD Protector, flow control, extend mode, active cooling, metal housing | Compliant Standards: IEEE 802.3i, IEEE 802.3u, IEEE 802.3z, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x | Power: AC 100-240 V | Dimensions (WxDxH): 32 cm x 20.7 cm x 4.5 cm | Weight: 2.29 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950