

## TP-Link Festa F61-Outdoor, Access Point



Model: Festa F61-Outdoor

Manufacturer: TP-LINK

EAN: 8885021370187

Product Code: 304052

## R2,510

Produktbeschreibung Festa Access Points bieten Business-Class-Funktionen mit verbraucherorientierter Einfachheit. Unsere kostenlose cloudbasierte zentrale Verwaltung ist über die Festa-App oder das Web zugänglich und bietet wesentliche Funktionen für kleine Unternehmen ohne die Komplexität, die für größere Operationen erforderlich ist. WiFi 6 bietet OFDMA und MU-MIMO, um mehrere Clients in überlasteten Umgebungen zu bedienen. Der Gigabit-Port sorgt für schnelle Konnektivität im gesamten Netzwerk für eine reibungslose Netzwerkverbindung. Mit drahtloser Mesh-Technologie benötigen Sie keine zusätzlichen Ethernet-Kabel, um zusätzliche APs im Abdeckungsbereich zu verlinken. Mit PoE-Unterstützung integriert ein einziges Kabel mühelos Daten und Strom, wodurch die Notwendigkeit zusätzlicher Verkabelung entfällt. Art.-Nr.: 100092747 Typ: Access Point | EAN: 8885021370187 | Hersteller-Nr.: Festa F61-Outdoor | Bauform: Deckenmontage | Einsatzbereich: Business | Anschlüsse: 1x (davon: 1x 10/100/1000) | WLAN: Wi-Fi 3 (802.11a), Wi-Fi 3 (802.11b), Wi-Fi 3 (802.11g), Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) - (2.4 GHz, 5 GHz) | Bedientasten: Reset | Stromversorgung: Netzteilanschluss | Feature: WLAN-Funktionen: Seamless Roaming, Beamforming, Automatic Channel Selection, OFDMA, Band Steering, Load Balance, Airtime Fairness, RADIUS Accounting, Wireless Schedule, Static IP/Dynamic IP, Rate Limit:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Based on SSID/Client, Multiple SSIDs: 16(8 on each band), Enable/Disable Wireless Radio, Enable/Disable SSID Broadcast, Guest Network, Transmit Power Control: Adjust Transmit Power on dBm QoS (WMM) || WLAN-Sicherheit: Captive Portal Authentication, Access Control, Wireless Isolation Between Clients, 802.1X Support, VLAN | Weitere Informationen: Wetterfest: IP67, Firmware update via Web, NTP, Centralized Management, APP support: Festa App, Cloud Access: Free cloud, LED abschaltbar, SNMP: v1, v2c, v3, Lokales/Remote-Systemprotokoll, SSH, Zero-Touch Provisioning | Zubehör: Netzadapter, Decken-/Wandmontage-Kit, Installationsanleitung | Abmessungen: Breite: 106,5 mm x Höhe: 280,4 mm x Tiefe/Länge: 63,5 mm | Gewicht: 780 Gramm

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950